

Tender documents For

New Glow Sign Board/Fascia Change/New Retro Reflective Sign Board/New Retro Reflective Indicator Board/Repairing of Indicator Board with Retro or Vinyl/other Repairing Work of Glow Sign Board in Kanpur Dehat Region

> Baroda U. P. Bank Regional Office, (Kanpur Dehat Region), Nabipur, Jainpur, Kanpur Dehat-209311 E-mail Id - pe.rokand@barodauprrb.co.in Mob: 7311149818

> > (S.M.ALAM) Regional Manager

BARODA U. P. BANK

Regional Office- Nabipur, Jainpur Kanpur Dehat-209311



Date: 05-02 -2021

BUPB: RO: P&E: RFP: GLOWSHINE/INDICATOR: 2020-21/

> TENDER FOR NEW SUPPLY & REPAIRING WORK OF NEW SIGNAGE WORK (GLOW SIGN BOARD), REPLACEMENT OF OLD FLEX & VINYL IN EXISTING SIGNAGES (BACKLIT SIGNAGE). NEW RETRO REFLECTIVE SIGN BOARDS, NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS, REPAIRING OF LOLLIPOP/INDICATOR BOARDS WITH RETRO REFLECTIVE AND VINYL, OTHER REPAIRING WORKS OF GLOW SIGN BOARD WITH INSTALLATION AND PROPER REPAIRING.

- ➤ BARODA U. P. BANK, REGIONAL OFFICE, KANPUR DEHAT INVITES SEALED TENDER FOR NEW SIGNAGE WORK (GLOW SIGN BOARD), REPLACEMENT OF OLD FLEX & VINYL IN EXISTING SIGNAGES (BACKLIT SIGNAGE). NEW RETRO REFLECTIVE SIGN BOARDS, NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS, REPAIRING OF LOLLIPOP/INDICATOR BOARDS WITH RETRO REFLECTIVE AND VINYL, OTHER REPAIRING WORKS OF GLOW SIGN BOARD WITH INSTALLATION AND PROPER REPAIRING AT OUR BRANCHES/OFFICES (NO. OF BRANCHES/OFFICES 60 LIST ENCLOSED WITH ADDRESS) SITUATED AT KANPUR DEHAT DISTRICT.
- ❖ SPECIFICATIONS FOR NEW SUPPLY & REPAIRING WORK OF SIGNAGE WORK: AS ENCLOSED.
- * ACCEPTABLE BRAND FOR NEW SUPPLY & REPAIRING WORK: ANNEXURE ENCLOSED.
- * ARTICLES SHOULD BE OF STANDARD QUALITY, AS SPECIFIED IN ANNEXURE.

THE CONTRACTOR



ELIGIBILITY:

- Only those vendors who have minimum three years experience of sale, service & repairing of NEW SIGNAGE WORK (GLOW SIGN BOARD), REPLACEMENT OF OLD FLEX & VINYL IN EXISTING SIGNAGES (BACKLIT SIGNAGE), NEW RETRO REFLECTIVE SIGN BOARDS, NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS, REPAIRING OF LOLLIPOP/INDICATOR BOARDS WITH RETRO REFLECTIVE AND VINYL, OTHER REPAIRING WORKS OF GLOW SIGN BOARD WITH INSTALLATION AND PROPER REPAIRING.
- The Bidder should have local service support office at Kanpur Dehat or area of Bank's operations.
- Experience with any PSU/Govt. for such type of work with satisfactory work done certificate or as acceptable by Bank.

WARRANTY:

- > 5/10 years (as per specification enclosed) from the date of installation.
- ➤ In the event of becoming defective within warranty period, vendor would be required to provide a new replacement at without any cost to the bank.
- > Vendor will be responsible for service/replacement during warranty period.

VALIDITY OF RATES:

- The Rate Contract with the selected vendor will be valid up to a period of Two Year i.e.31-03-2023 from the date of acceptance of the rates.
- ➤ The bank (Regional office) will place the orders and delivery with installation will be at our branches/offices in the Kanpur Dehat Region (city & villages). Bidder shall make necessary arrangements for processing the orders.

OTHER CONDITIONS:

- > The registration number of the firm along with the GSTIN no. allotted by the authorities must be submitted.
- > PAN number of the firm allotted by the income tax authorities should be submitted (without which the vendor's bid would become invalid and same shall be rejected).
- Conditional tenders shall not be accepted on any ground and shall be rejected straight away.
- Any deviation of the conditions given by the purchaser will not be accepted and the bid will be rejected without assigning any reasons.
- > If any clarification is required the same should be obtained before submitting the bid.
- The entire tender document must be signed with the seal and attached as mark of acceptance of terms and conditions.





BID SUBMISSION:

- The sealed tenders must reach the <u>REGIONAL MANAGER</u>, <u>BARODA U. P. BANK</u>, <u>REGIONAL OFFICE KANPUR DEHAT</u>, <u>NABIPUR</u>, <u>JAINPUR</u>, <u>KANPUR DEHAT-209311 COMPLETE IN ALL RESPECT LATEST BY 5:00 PM ON OR BEFORE 03.03.2021</u>. Bids received after that shall not be entertained.
- > Bids must be submitted through hand to hand or through registered Post/Courier.
- > Bid must be delivered at the given address within given time frame.
- > The bid must contain two Envelopes as per procedure given below.

FIRST ENVELOPE MUST CONTAINS ALL THE DOCUMENTS GIVEN BELOW:-

- 1. Details of infrastructure for providing proper services and supply.
- 2. Attested photocopy of document of registration of firm along with GSTIN No.
- 3. Photo copy of PAN Number duly attested.
- 4. Photo copy of GSTIN number duly attested.
- 5. The entire tender document duly signed by the vender as a mark of acceptance of term and conditions of the tender document.
- 6. All the documents should be self attested along with stamp of the Firm.
- ➤ IF ANY OF THE ABOVE DOCUMENTS IS/ARE NOT SUBMITED OR IF SUBMITED BUT IS NOT DULY ATTESTED, THE BID WILL BE REJECTED & PRICE BIO WILL NOT BE OPENED.
- > IT MUST BE MENTIONED ON ENVELOPE "DOCUMENT SUBMITTED FOR BID OF NEW SUPPLY & REPAIRING WORK OF SIGNAGE (GLOW SIGN BOARD)"

SECOND ENVELOPE MUST CONTAIN ALL THE DOCUMENTS GIVEN BELOW:

SECOND ENVELOPE MUST CONTAIN only bid and nothing else.

- The price must be submitted on the prescribed format of annexure-I (Section A, B, C, D, E, F, G) along with document.
- Price bid will not be accepted on any other format or document.
- ➤ It must be clearly mentioned "PRICE BID OF "DOCUMENT SUBMITTED FOR BID OF NEW SUPPLY & REPAIRING WORK OF SINGAGE (GLOW SIGN BOARD)"



क्षेत्रीय कार्यालय, नबीपुर, पोस्ट-जैनपुर, कानपुर देहात-209311, दूरभाषः 0511-220266 Regional Office, Nabipur, Post – Jainpur, Kanpur Dehat-209311, Telephone-0511-220266 e-mail: rokand@barodauprrb.co.in



▶ BOTH TWO ENVELOPES MUST BE KEPT IN THIRD SEALED ENVELOPE AND SUPERSCRIBED "BID FOR "DOCUMENT SUBMITTED FOR BID OF NEW SUPPLY & REPAIRING WORK OF SIGNAGE (GLOW SIGN BOARD)"

PROCESS & TIME FRAME:

Bids will be opened on **08-03-2021** at **03:00 PM**, at Regional office, Kanpur Dehat, Bidders can depute their representative (only one) to present at the time of opening of bid & process. No separate intimation will be given in this regard to the bidders.

EVALUATION OF BIDS:

Quoting incredibly low value of items with a view of subverting the tender process shall be rejected straight away.

DELIVERY:

- 1. Delivery at site should be made within 1 month of date of placement of order which should be extended for next 07 days in special case like Natural calamities (heavy rain, earthquake, flood etc), In case of some urgent requirement of the bank, the same may be delivered urgently.
- 2. No extra freight or any other charges will be paid.
- 3. Each Glow Sign Board/Fascia Change/New Retro Reflective Sign Board/ New Retro Reflexive Indicator Board/ Repairing of indicator with new Retro Reflective Sheet/other Repairing work should be clearly marked with manufacturing date, installation date, warranty date, vendors name and Telephone Number.

LIQUIDATED DAMAGES:

In case of delay in supply/attending complaint, Liquidated <u>damages@1.50%</u> of the order value per week would be imposed after 7 days supply/complaint period. (Example: Rs.750/- will be deducted for delay to attend complaint within one week for an order value of Rs. 50,000/- and like).

If delivery of order is not supplied within stipulated time from the date of order i.e. 1 month. Order will & automatically cancelled on vendor's own cost.

SINGLE POINT OF CONTACT FOR SUPPORT:

Bidder has to provide details of single point of contact viz, designation, address, e-mail address, telephone/mobile No. for communicating and service support as per Annexure-II

19 QT Q (

क्षेत्रीय कार्यालय, नबीपुर, पोस्ट-जैनपुर, कानपुर देहात-209311, दूरभाषः 0511-220266 Regional Office, Nabipur, Post – Jainpur, Kanpur Dehat-209311, Telephone-0511-220266 e-mail: rokand@barodauprrb.co.in



PAYMENT TERMS:

> Payment will be made after successful installation of Sign Board/Indicator.

> The selected bidder will have to deposit 5% of total bill amount before payment in form of FDR with our bank as security money. The selected Bidder will have to sign an agreement with the Bank.

> The Bank will pay invoices within a period of 10 days from the date of receipt of undisputed invoices.

TDS deduction as per Income tax department.

RIGHT TO REJECT BIDS:

- I. Bank reserves the right to accept or reject any quotation or cancel the entire process at any stage without assigning any reason whatsoever. The bank does not bind itself to accept the lowest of any quotation and reserves to itself the right to accept or reject any or all quotations either in whole or part, without assigning any reason for doing so.
- II. The selected bidder is found to be unsatisfactory response/performance.
- III. If the supply delayed by more than one weeks from the due date of delivery or if deductions on account of liquidated damages exceeds more than 5% of the contract value.

REQUEST FOR INFORMATION:

All queries relating to the RFP, technical or otherwise, must be either in writing or by email only-pe.rokand@barodauprrb.co.in for any CLARIFICATION CONTACT- Regional office; Nabipur, Jainpur, Kanpur Dehat – 209311, or P&E Deptt–7311149818.





PRICE QUOTATION

	Annexure-
NAME OF BIDDER:	
ADDRESS FOR CORESSPONDENCE:	
PERMANENT ADDRESS:	
LOCAL KANPUE DEHAT BASED ADDRESS:	
LOCAL KANI CE DEHAT BASED ADDRESS.	
TELEPHONE NO./MOB:	
TAN/DIN/DANINO.	
TAN/PIN/PAN NO:	
FAX NO:	
E-MAIL:	
Experience:	

ME 192 SA G



ITR for 3 years attac	ened:		
			- 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1 × 1
Balance sheet for 3 y	ears attached:		
Experience with PSU	J/Govt.:		
	y.		
(Copy Enclosed):			
Satisfactory Work D	one letter attached	<u>l</u> :	

9 R C



BILL OF QUANTITIES - SECTION- A (FOR NEW SIGNAGE WORK)

SI No	Description	QTY	Unit	Rate	Amount
A.	GLOW SIGN BOARD		3 7		
	Providing and Fixing of Flexible Substrate of make, respective codes and specifications given in tender for use in Back lit signages. Cost of fascia (Backlit flex) including labour charges for				
10.0	plotting & pasting, tensioning ("L" angle system) with signages	1	S.Ft.		
1.1	cabinet, electrical items, Digital Timer and fixing complete as per specification.				7.
	Replacement Warranty for the Fascia materials for a period of 5 years. The Parent Manufacturer/their representative has to inspect				1
	the site and certify for quality, workmanship and materials in the Warranty card.				-
a.	SCAFFOLDING WORKS				
	(No Extra charges for height below 25 ft.)				10 m
	Cost of Scaffolding for Hoisting Signages, for height above 25 fts. (1) No payments will be made for scaffolding for Signage installations/ fascia change up to a height of 25 feet from the floor level to bottom of Signage.				
	2) If the signage is to be installed on roof top of a building, where space for working is available, no extra payments will be paid for the sake of lift/ scaffolding charges.	1	S.Ft.		
	The area of Scaffolding will be measured from the bottom of signage to Ground level x Length of signage		# 4		

BILL OF QUANTITIES FOR FASCIA CHANGE- SECTION- B

Sr.	Description	QTY	Unit	Rate	Amount
В.	REPLACING OF OLD FLEX & VINYL OF EXISTING SIGNAGES		-7%		20
	(Backlit signage) (L1WILL BE DECIDED FOR FLEX CHANGE RATE ONLY)		31	i e i	L. 1
	Removal of old Flex and Vinyl and providing new flex and vinyl is using the present art work approved and retaining the existing Boxing / MS Framing.				
1.1	Replacement Warranty for the Fascia materials for a period of 5 years. The Parent Manufacturer / their representative has to inspect the site and certify for quantity, workmanship and materials in the warranty card.	1	S.Ft.		

Date:

Sign & Stamp of Vendor

19 mg 1



BILL OF QUANTITIES FOR NEW RETRO REFLECTIVE SIGN BOARDS- SECTION- C

Sr.	Description	QTY	Unit	Rate	Amount
C.	RETRO REFLECTIVE SIGN BOARDS				
1.1	Manufacturing, supplying & installation of retro reflective sign boards made up of 2 mm thick aluminum sheet, face to be fully				
	covered with high intensity encapsulated type heat activated retro reflective sheeting conforming to type-IV of ASTM-D 4956-01 in approved colour combination including subject matter, (bi-lingual), symbols and borders etc. as per IRC:67:2001, pasted on substrate by		-		
	an adhesive backing which shall be activated by applying heat and pressure conforming to class -2 of ASTM-D- 4956-01 and fixing the	1	S.Ft.		
	same with suitable sized aluminum alloy rivets @ 20 cm c/c to back back support frame of M.S. angle iron of size 25x25 x3 mm along		Z.	4 3	
	With theft resistant measures, mounted and fixed with 2 Nos. M.S. angles of size 35x35x5. Backside of aluminum sheet to be painted			ti d	
	with two or more coats of epoxy paint over and including appropriate priming coat including all leads and lifts etc. Warranty for the retro Reflective Signboard for a period of 10 years	¥ 8			# 22

BILL OF QUANTITIES FOR NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS- SECTION- D

Sr.	Description		Unit	Rate	Amount
D.	RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS – DOUBLE SIDE				
1.1	Manufacturing, supplying & installation of retro reflective Lollipop/indicator boards (double side) made up of 2 mm thick aluminum sheet (3x2 feet, Rectangular shape), Brand 3M, Avery Dennison, conforming to ASTMD-4956, with double M.S. Tee		S.Ft.	8	
	section ISMT 50x50x6x mm of support length of 2500 mm. warranty for boars for a period of 10 years.				

Date:

Sign & Stamp of Vendor

AND A Q



BILL OF QUANTITIES FOR NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS- SECTION- E

Sr.	Description	QTY	Unit	Rate	Amount
E.	VINYL LOLLIPOP/INDICATOR BOARDS – DOUBLE SIDE				for the
1.1	Manufacturing, supplying & installation of Vinyl Lollipop/indicator boards (double side) made up of 2 mm ACP sheet (3x2 feet, Rectangular shape), Vinyl 3M, (Scotchal 3630 series, 3650series, 7725 series) with double M.S. Tee section ISMT 50x50x6x mm of support length of 2500 mm. warranty for boars for a period of 5 years.		S.Ft.		

BILL OF QUANTITIES FOR FASCIA INDICATOR BOARD- SECTION- F

Sr.	Description	QTY	Unit	Rate	Amount
F.	REPLACING OF OLD VINYL OF EXISTING SIDE INDICATOR		10		
1.1	Removal of Old Flex and Vinyl and providing new sheet of Retro reflective Lollipop/Indicator boards (double side) made up of 2 mm Thick aluminum sheet. Brand 3M, Avery Dennison, Conforming to AS TMD 4956. Replacement Warranty for the Fascia materials for a Period of 10 years. The Parent Manufacturer / their representative has to inspect the site and certify for quality, workmanship and materials in the Warranty card. flex and vinyl is using the present art work approved and retaining the existing Boxing / M.S. Framing, All the metal portions of the existing MS Frame to be painted with one coat of antirust paint and 2 coats of white colour enamel paint,	1	S.Ft.		

Date:

Sign & Stamp of Vendor





BILL OF QUANTITIES FOR REPAIR & MAINTANCE - SECTION G

Sr.	Description	QTY	Unit	Rate	Amount
G.	Providing and Replacing of Electrical fittings & fixtures while replacing the Flex & Vinyl in case of damaged items. A sample quantity is mentioned below. Actual quantity as ser site conditions has to be replaced and got certified from the branch Head. (No Extra Changes for wiring etc. will be paid)				
1.1	LED Tube light – 36 watt (Philips/Osram/Havells)	NOS.	1		
1.2	LED Tube light Driver (Philips/Osram/Havells)	NOS.	-1		
1.3	Installing of Digital timer (L&T/MDS)	NOS.	1		
	No separate Vendor will be decided for repairing work. Two vendors who is lowest for new Signage and flex change will accept the rate of lowest amount quoted amongst all the vendors for repairing work.				

Only GST shall be paid extra as applicable.

Note:-

- 1. No extra payment shall be made for lift up to 25 ft. (bottom of the Signages) from floor level.
- 2. Scope of works at any location will be any one or more items from the above BOQ according to site condition.
- 3. Authorized Converter Certificate copy to be attached at the time of tender submission.
- 4. Vinyl/Flex/Retro Authorized distributor Material purchase order certificate to be produced at the time of invoice submission.
- 5. Flex /Vinyl/Retro Warranty certificate required at the time of invoice submission otherwise vendor payment will he hold by bank.
- 6. The Rates quoted will be valid for 2 Year, No Price escalation will be considered.
- 7. Billing is based on actual square footage / quantity of the used material in Signages, certified by the Branch concern staff / Branch Manager.

Date: Sign & Stamp of Vendor

W & & (



Annexure-II

ESCALATION MATRIX Delivery/Service Related Issue

SN	Name	Designation	Mobile No.	E-Mail Address
1.		First Level		
2.		Second Level	8	
3.		Third Level		
4.		Regional Head		

Any change in designation will be informed by us immediately.

Date:		Signat	ure with designation
		com	pany seal



TECHNICAL SPECIFICATIOMS FOR NEW SUPPLY (SUGGESTED)

- 1. SPECIFICATIO NS FOR FLEX SUBSTRATE AND VINYL TO BE USED FOR SIGNAGE.
 - A. FASCIA-FLEXIBLE SUBSTRATE: The properties are given in Table 1 below.

It shall have UV resistors added while manufacturing to prevent the whiteners turning yellow due to constant exposure to UV rays. The flex and Vinyl should be warranted for a period of five years from the date of completion against yellowing/graying of flex. Plasticizer migration, wicking of flex, fungus or mildew formation, vinyl peel-off, fading, shrinkage, cracking and crazing etc.

- **B. GRAPHICS:** Graphics shall be computer-cut with translucent vinyl matching the colour combination of Baroda U.P. Bank.
- C. The colour specification for the signage: Colour Pantone number (Baroda Vermillion) 1665C.
- D. Brand Make 3M/Avery Dennison/LG Hausys/or Equivalent.

Property	AL PROPERTIES OF FLEXIBI Specification	Test Method
Thickness	600 micron +/- 10 %	DIN 53353
Total Weight	700 gm/ sq.mtr. +/- 5 %	DIN 53353
Base Fabric	Polyester	
Yarn	1000 x 1000 Denier	DIN EN ISO 2060
Elongation	< 50 %	ASTM 882
Tensile Strength (L/W)	150/140 Kg./2.5 Cm	DIN 53354 (Cut Strip)
Tear Strength (L/W)	25/20 Kg.	DIN 53354 (Single Tongue)
Adhesion Strength (PVC+Fabric)	50 Kg./5 Cm	DIN 53357
Light Transmission	25 to 32 %	
Substrate	Polyester scrim embedded in a white pigmented vinyl (or PVC based)	

De OVER OF A



TABLE - 2 PHYSIC	AL PROPERTIES OF T	RANSLUCENT VINYL
Property	Specification	Test Method
Thickness (Including Adhesive)	80 mm ± 10%	Micrometer
Tensile Strength	400 ~ 1000 g/mm	ASTM 882
Elongation	100 ~ 300 %	ASTM 882
Peel adhesion (24 hrs)	1,200 g/in	180 peeling PSTC-1
Application temp.	10° C	18 to 25° optimum, on clean substrate
Gloss	30 ± 5	@60, in Machine Direction (ASTM D 2457)
Dimensional Stability	Max 0.5%	Adhered to Aluminum Plate, Length Direction (100°C oven, 2hr Average)
Release liner thickness	0.17 mm ± 0.08 mm	Micrometer
Colour	Baroda Vermillion Pantone 1665 C	

Note:-

- i. Written warranty shall be obtained for 5 years for per signage/site from the original manufacture through vendors/signage Contractor for Flex & Vinyl supply from date of installation. Vendors/ Signage contractor to Submit tender specific authorization from original Manufacturer for Flex Vinyl.
- ii. Flex/ Vinyl original Manufacturer should have presence in India either directly or through their subsidiaries by way of having its plants / sales offices in India.
- iii. Every signage warranty certificate submission shall be compulsory with execution invoice.
- iv. STANDARDS: All the materials shall conform to the required standards & safety aspects as specified in relevant ASTM/DIN/BIS standards wherever applicable.
- v. The sign boards have to be fixed at various heights from the ground level as per the requirement.

2. SIGN BOX SPECIFICATIONS:

i. SIGN CABINET STRUCTURE -FRAME WORK: The box (structure) should be fabricated using square MS tube 1" x 1" of 18 gauge (of Jindal, TATA or approved equivalent make) with primer and enamel painted. ISI grade GI Sheet of 24 gauge duly powder coated for side, top and bottom and 26 gauges for back should be used. Thickness of back-lit sign board should be minimum 9". Bird-proof vent holes to be provided on the GI sheets provided on the sides of the board to dissipate hot air. Aluminum drip cap with 2" projection to be provided on the top front edge of the sign board to protect the fascia from rain. All internal metal portions of the sign cabinet to be painted with one coat of Antirust paint and 2 coats of whitecolour enamel paint.



क्षेत्रीय कार्यालय, नबीपुर, पोस्ट-जैनपुर, कानपुर देहात-209311, दूरभाषः 0511-220266 Regional Office, Nabipur, Post – Jainpur, Kanpur Dehat-209311, Telephone-0511-220266 e-mail: rokand@barodauprrb.co.in



- ii. SIGN CABINET SUPPORT: The sign cabinet should be provided with suitable arrangements for fixing to existing wall surface or existing supporting structures available with suitable clamps, brackets, anchor bolts etc. The arrangements should be adequate to support the weight of the cabinet and to keep it firmly in position. The minimum requirement is that the signage frame work shall be anchored to the sunshade below using 'L' angle of 25mmx25mmx5mm thick equal angle in L shape at an interval of every 5 fest (of TATA, Jindal or equivalent approved make). Further the board should be anchored from top to the back wall using suitable steel/GI wire of minimum 8mm thick. AII exposed clamps; brackets etc shall be painted with two coats of synthetic enamel paint over a coat of primer. Nothing extra will be paid for fixing the cabinet in position,
- iii. WELDING SPECIFICATIONS: Branded welding rods should be used for welding the joints. Welding rod should be preheated prior to welding. Preheating the welding rods enables uniform & smooth flow of the welding material in the joints. If welding is done with preheated rod there will be no formation of open fissures in the joint due to smooth flow of welding material. Open fissures cause weakening of joints. Welding has to be done across the full cross section of the MS hollow pipe.
- iv. PROTECTION OF THE FRAME: The entire frame of the sign cabinet post welding has to be grinded around the welding joints to remove spurs and undulations if any created during welding. Post grinding the joints, the MS pipe has to be painted with zinc chromate primer and 2 coats of synthetic enamel paint of white shade.
- v. FASTENERS: The fasteners used shall be uniform and at such spacing that it does not spoil the appearance of the signage looking from the bottom or the sides. The head of the screw shall have capping of stainless steel.
- vi. SIGN BOX TENSIONING SYSTEM: A suitable tensioning system should be used for stretching flexible substrate on the front part of the sign box such that there should not be any shrinkage, cracking and crazing. Flex wrinkling/ bends shall not occur post tensioning. To ensure that the flexible substrate is tensioned uniformly an extruded aluminum tensioning system with Allan key tensioning system with rubber beading should be adopted. The sign face shall be tensioned with tensioning system all along the length and width of the sign.

3. PROCESS OF PASTING VINYL STICKERS OVER THE FLEX SUBSTRATE:

The pasting vinyl stickers over the flex substrate shall be undertaken with all care and techniques such as using pre mask tapes to the vinyl before initiating the fixing of the same over the flex, it shall be ensured that vinyl is properly aligned to the flex without any gaps at the outer edges, there are no air bubbles, etc., The workmanship shall be of high standards and engineering.

4. FIXING OF THE SIGNAGES AND SAFETY AT SITE: The signage providers shall duly assess the site condition for fixing securely by appropriate means using necessary clamp, hooks, fasteners and including minor civil works necessary at site. The entire signage so fixed at site shall withstand high wind pressure depending upon the actual

EN ON M &



locations / floor in which it is installed, It shall also be the responsibility of the signage solution provider for the safety of the installation, the signage till they accepted by the bank. While executing the work the labour force used shall comply with labour laws and all necessary safety measures shall be undertaken like using scaffolds, ladders, safety belts, helmets, gloves, appropriate tools. Suitable precautions shall be taken against overhead power lines, slippery surface or such other hazards which may be in the close proximity to the premises / site. Any damages to the signage during the process of installation will result in rejection of the signage end the same shall be replaced at their own cost.

ME ON ME &



5. ELECTRICAL COMPONENTS:

Specification of single Sided LED Modular Lights:

Sr. No.	Parameters	Significance	Desirables			
	Specifications for LED Module					
1	Make for LED chip	To have creditable and quality products	Nichia/Cree/Lumileds/C sr am			
2	Make of LED Module	To have creditable and quality products	Orsam/Lighting Technologies/Tridonic			
3	LED Module Product Name	To have creditable and quality products	OrsamBackLED M Plus G15/LT Maze SLHO/T ri doni cT ALEXX chain Crystal Classic P541			
4	Colour CCT	CCT defines the color which the light will Emit 2000-3000K: Warm White; 3000- 5000K:Day light color; 6000-7000K:Pure white color; >7000K:Cool white color	6500Kelvin(K)			
5	Certifications of LED Chip	To check brightness	LM80			
6	Beam Angle	A beam angle defines the distance at which the module can be kept behind the vinyl to have uniform brightness	>=150 Degree (Angle of Irradiation)			
7	Mounting Technology	LED Mounting-compactness by SMD Module Mounting-Modules should not come out with heating and wind pressure	Surface Mounted Device (SMD)			
8	Watt/Module	Wattage per module helps to calculate total power our signage will consume	0.72 W/0.75 W			
9	LED Module Per Sqft in Signage	To check no. of LED's used in a Signage	3 Module/Per Sqft			
10	System efficancy (Lm/W) or Lumin Output	It is a measure of the efficency of a lighting system.	>95-100 Lm/W			
11	Operating temperature	To ensure proper functioning of signages at various locations.	-40 degree C to +65 degree Centigrade			
12	LED Module life	It indicates the number of hours before the luminance drops to 70% of initial output	Min 50000 Burnig Hrs (L70/B50) at 85 degree Centigrade			
13	Housing Module Material	Housing module material selected for holding the LED chip and lens	Poly carbonate (PC)/ RoHS (Reduction of hazardous substances) Compliant material to be used.			



14	CRI (Colour Rendering Index)	To the colour rendering Index (CRI) is the index of LED tubelight compared with natural light	>=80	
15	Protection class	IP defines the protection of modules for dust and water	IP 66	
16	Cetifications and stadards for moudules	No hazardous substance and meeting international standard	BIS/LM79/LM80	
17	LED Module Certification		YES	
18	Internal drivers in Modules		Yes	
19	Optics		The chip should have a optical lens	
		pecification for LED Driver		
20	LED Driver	Converts I/P AC voltage to DC Voltage for LEDs	Osram/Lighting Technologies / Tridonic	
21	LED Driver Name	Converts I/P AC voltage to DC Voltage for LEDs	Osram Optotronic Series / Lighting Technologines (LT)/ Tridonic TALEXX Converter	
22	Driver Wattage (W)	Wattage at which driver I designed	40w/60w/100w/120 w	
22	Driver wattage (w)	To Protect the system from fluctutation in	In built Min. 6 KV (
23	Surge protection (in KV inbuilt)	Voltage	Line to ground)	
24	Supply Voltage for drivers (Input	Voltage range at which LED drivers function	90V-300V	
24	Voltage) Protection	Voltage range at which LED drivers function	Over Voltage , Over Current , Over Temp. Short Circuit	
26	IP rating	IP defines the protection of modules for dust and water	Min. IP 67	
27	Output Power		40w/60w/100w/120 w	
28	Standards for LED Driver	International Standard	CE(European Conformity)/CB/C- Tick/UL (Under Written Laboratory) EN 55015, EN 62031, EN 61000-3-2, EN 61000-33, EN 61000- 4-5, EN 61547, EN 61547-1, EN 61347-2- 13 or As per IEC	
29	Cable for Modules	Standard Cable to avoid heat and fire	AWG 18	
30	Cabel For Driver	Standard Cable to avoid heat and fire	AWG 18 / AWG 17	
31	Warranty	to ensure quality and life of product	5 years warranty on LED Modules and Drivers	
32	THD (Total Harmonic Distortion)		< 10%	
33	Short Circuit Protection		Automatic , Reversible	



34	Overload Protection		Automatic , Reversible
35	Over Temperature Protection		Automatic , Reversible
36	UL/CE/ROHS/ENEC/BIS		Yes
37	Input Under Voltage		Shut down and Auto restart
38	Manufacturer		Osram/Lighting Technologies / Tridonic
Protection Rating		Description	
IP66		Fully Protected from dust and protected ag powerful jets of water	7
IP67		Fully Protected from dust and can also withsta m (about 3.3 feet) of static water for	

Note:-

- 1. Written warranty shall be obtained for 5 years for per signage / site from the original manufacturer through vendors /signage contractor for the led modules and power supply from date of installation.
 - Vendor / signage contractor to submit tender specific authorization from original manufacturer for LED Modules and powr slupply.
- 2. Every Signage warranty certificate submission shall be compulsory with execution invoice
- 3. STANDARDS: All the materials shall conform to the required standards & safety aspects as specified in relevant ASTM/BIS standards wherever applicable
- 4. The sign boards have to be fixed at varous heights from the ground level as per the requirement.





15. RETRO REFLECTIVE SIGN BOARDS & LOLLIPOP/INDICATOR BOARDS

Specification - Retro Reflective Sign Box	ard (Laminated)		
Structure Pipe	1 inch		
Sheet	Aluminium composite pannel (ACP) – 2 mm		
Base	Retro Reflective sheet colour white		
Retro Sheet	HIP (High Intensity Prismatic), Type – 4, Class B		
Brand	3 M, Every Dennision, Conforming to ASTMD4956		
Specifcation - Retro Reflective Lollipop/	Indicator Boards (Laminated) - Double Side		
ACP Sheet	2mm (3x2 feet, Rectangular Shape)		
Base	Retro Reflective sheet colour white		
Retro Sheet	HIP (High Intensity Prismatic), Type – 4, Class B		
Brand	3 M, Every Dennision, Conforming to ASTMD4956		
M.S. Tee Section	Double M.S. Tee section ISMT 50x50x6 mm of support length of 2500 mm		
Specification - Vinyl Lollipop/Indicator	<u> </u>		
ACP Sheet	2mm (3x2 feet, Rectangular Shape)		
Base	Vinyl 3M (Scotchal 3630 series, 3650 series, 7725 series)		
M.S. Tee Section	Double M.S. Tee section ISMT 50x50x6 mm of support length of 2500 mm		

Note :-

- 1. Written warranty shall be obtained for 10 years for per signage/site from original Manufacturer through vendors/signage contractor for retro reflective sign boards/indicator boards and 5 years for vinyl indicator boards per board/site from date of installation. Vendors/Signage Contractor to submit tender specific authorization from Origional Manufacturer for ACP and Retro.
- 2. Every signage warranty certificate submission shall be compulsory with execution invoice.
- **3.** STANDARDS: All the materials shall conform to the required standards and safety aspects as specified in relevant ASTM/BIS standards wherever applicable.
- 4. The sign boards have to be fixed at various heights from the groun level as per the requirement.
- 5. Reference 10'x3',12'x3',15'x4',20'x4' & 25'x4'



REGION: KANPUR DEHAT

Name OF BRANCHES

SR	NAME OF BRANCH	शाखा का नाम हिन्दी में	DISTRICT	MOBILE/CUG NUMBER
1	AKBARPUR	अकबरपुर	KANPUR DEHAT	7310108590
2	AMAULI KURMIYAN	अमौली कुर्मियान	KANPUR DEHAT	7310108591
3	AMRAUDHA	अमरौधा	KANPUR DEHAT	7310108592
4	ANGADPUR	अंगदपुर	KANPUR DEHAT	7310108593
5	ASALATGANJ	असालतगंज	KANPUR DEHAT	7310108594
6	AUNAHA	औनहा	KANPUR DEHAT	7310108595
7	BACHEET JASU	बचीत जस्	KANPUR DEHAT	7310108596
8	BAGHPUR	बाघपुर	KANPUR DEHAT	7310108597
9	BAIRI SAWAI	बैरी सवाई	KANPUR DEHAT	7310108598
10	BAN BAZAR	बान बाज़ार	KANPUR DEHAT	7310108599
11	BARAUR	बरौर	KANPUR DEHAT	7310108601
12	BAMHRAULI GHAT	बम्हरौली घाट	KANPUR DEHAT	7310108602
13	BUDHAULI	बुधौली	KANPUR DEHAT	7310108603
14	CHAURA	चौरा	KANPUR DEHAT	7310108604
15	DILWAL	डिलवल	KANPUR DEHAT	7310108605
16	DOHRAPUR	दोहरापुर	KANPUR DEHAT	7310108606
17	GAHLON	गहलों	KANPUR DEHAT	7310108607
18	GALUAPUR	गलुआपुर	KANPUR DEHAT	7310108608
19	GUJRAI	गुजरई	KANPUR DEHAT	7310108609
20	GURGAON	गुरगाँव	KANPUR DEHAT	7310108610
21	JAITPUR	जैतपुर	KANPUR DEHAT	7310108611
22	JHINJHAK .	झींझक	KANPUR DEHAT	7310108612
23	KAINJEHRY .	कहिंजरी	KANPUR DEHAT	7310108613
24	KANDHI	कांधी	KANPUR DEHAT	7310108614
25	KAUROO	कौरू	KANPUR DEHAT	7310108615
26	KHAMAILA	खम्हैला	KANPUR DEHAT	7310108616
27	LALPUR	लालपुर	KANPUR DEHAT	7310108617
28	MAITHA STATION	मैथा स्टेशन	KANPUR DEHAT	7310108618
29	MANGALPUR	मंगलपुर	KANPUR DEHAT	7310108619
30	MOHANA	मोहाना	KANPUR DEHAT	7310108620
	MOHD. KHERA	मोहम्मदपुर खेड़ा	KANPUR DEHAT	7310108621
32	MOHD. MALASA	मोहम्मदपुर मलासा	KANPUR DEHAT	7310108622
	MOOSANAGAR	मूसानगर	KANPUR DEHAT	7310108623
	MUNGISAPUR	मुंगीसापुर	KANPUR DEHAT	7310108624
7	NASEERPUR SIKANDRA	नसीरप्र सिकंदरा	KANPUR DEHAT	7310108625



REGION: KANPUR DEHAT

Name OF BRANCHES

SR	NAME OF BRANCH	शाखा का नाम हिन्दी में	DIŞTRICT	MOBILE/CUG NUMBER
36	NABIPUR	नबीपुर	KANPUR DEHAT	7310108626
37	NAUHA NAUGAON	नौहा नौगाँव	KANPUR DEHAT	7310108627
38	NONAPUR	नोनापुर	KANPUR DEHAT	7310108628
39	PAHARIPUR	पहाड़ीपुर	KANPUR DEHAT	7310108629
40	PARSAULI ·	परसौली	KANPUR DEHAT	7310108630
41	PINDARTHOO	पिन्डार्थू	KANPUR DEHAT	7310108631
42	POKHRAYAN	पुखरायां	KANPUR DEHAT	7310108632
43	RASOOLPUR GOGUMAU	रस्लपुर गोग्मऊ	KANPUR DEHAT	7310108633
44	RAEPUR(SANDALPUR)	रायपुर	KANPUR DEHAT	7310108635
45	RAIPUR	रायपुर	KANPUR DEHAT	7310108634
46	RANIYA	रनिया	KANPUR DEHAT	7310108636
47	RANJITPUR	रंजीतपुर	KANPUR DEHAT	7310108637
48	RASOOLABAD	रसूलाबाद	KANPUR DEHAT	7310108638
49	RURA	रूरा	KANPÚR DEHAT	7310108639
50	RURWAHAR	रुरवाहार	KANPUR DEHAT	7310108640
51	SARAI	सरांय	KANPUR DEHAT	7310108641
52	SARGAON BUJURG	सरगांव बुजुर्ग	KANPUR DEHAT	7310108642
53	SATTI	सट्टी	KANPUR DEHAT	7310108643
54	SHAHJAHANPUR	शाहजहाँपुर	KANPUR DEHAT	7310108644
55	SHIVALI	शिवली	KANPUR DEHAT	7310108645
56	SIMRAMAU	सिमरामऊ	KANPUR DEHAT	7310108646
57	SITHMARA	सिठमरा	KANPUR DEHAT	7310108647
58	TISTI	तिस्ती	KANPUR DEHAT	7310108648
59	USARI	उसरी	KANPUR DEHAT	7310108649
60	REGIONAL OFFICE KANPUR DEHAT	क्षेत्रीय कार्यालय कानपुर देहात	KANPUR DEHAT	7311149818

