



**बड़ौदा यू.पी.बैंक**  
**Baroda U.P. Bank**

प्रधान कार्यालय : बुद्ध विहार व्यावसायिक योजना, सारामंडल, गोरखपुर-273016  
शिथिल कार्यालय : ए-1, सिविल लाइन्स, रायबरेली-229001, फोन : 0535-2702075

**प्रयागराज क्षेत्र अन्तर्गत आने वाली शाखाओं हेतु ग्लो साइन बोर्ड /नॉन ग्लो साइन बोर्ड व इन्डिकेटर बोर्ड हेतु निविदा**

अवगत कराना है कि हमारे क्षेत्रान्तर्गत 87 शाखाओं व क्षेत्रीय कार्यालय की आवश्यकता के अनुसार पूर्व में लगे ग्लो साइन बोर्ड/ नॉन ग्लो साइन बोर्ड व इन्डिकेटर बोर्ड के स्थान पर बैंक के निर्धारित मानको के अनुसार नवगठित बैंक "बड़ौदा यू.पी.बैंक" के नाम व लोगो के **Glow Sign Board,Fascia Change,Ratro reflective Sign Board,Retro Reflective Lollipop-Indicator Board (Double Side), Vinyl Lollipop Indicator Board-(Double Side) आदि के Installation, Repairing & Maintenance** का कार्य कराया जाना है।

उपरोक्त कार्य हेतु हमारे द्वारा दिनांक 15.01.2021 को टेन्डर नोटिस जारी किया गया था जिसे दिनांक 15.02.2021 को खोला जाना था जिसकी प्रक्रिया अपरिहार्य कारणों से सम्पन्न नहीं करायी जा सकी | (All the Quotation/Tender earlier received will remain unopened & kept with our records. ) तत्क्रम में हमारे द्वारा उपरोक्त कार्य हेतु पुनः टेन्डर आमंत्रित किया जा रहा है जिसके क्रम में इस पत्र के साथ संलग्न **Technical Specification** के अनुसार पूर्ण रूप से भरा हुआ अपना कोटेशन सीलबन्द लिफाफे में दिनांक **09.03.2021 को सायंकाल 5:00 बजे तक** इस कार्यालय को निम्न पते पर उपलब्ध कराएँ। उक्त तिथि के पश्चात् प्राप्त कोटेशन पर विचार नहीं किया जायेगा | टेन्डर दिनांक 10.03.2021 को सायं 3.00 बजे क्षेत्रीय कार्यालय में खोला जायेगा।

**बड़ौदा यू.पी.बैंक**

क्षेत्रीय कार्यालय 3D ताशकंद मार्ग सिविल लाइन्स प्रयागराज (इलाहाबाद) 211001


टेन्डर प्रक्रिया के पश्चात् Successful bidder को उपरोक्त कार्य के सापेक्ष बैंक द्वारा दिए गये मानको के अनुसार आवश्यक Items की संस्थापना के पश्चात् वारंटी अवधि हेतु Invoice मूल्य की 5 प्रतिशत राशि को रिटेंशन मनी के रूप में रोकते हुए नियमानुसार टी डी एस की कटौती करते हुए भुगतान किया जायेगा।

**अन्य शर्तें निम्नवत हैं -**

1- उक्त कार्य हेतु किसी बैंक अथवा सरकारी संस्था में कम से कम 3 वर्षों का अनुभव होना चाहिए,जिसकी पुष्टि हेतु बैंकों /संस्थानों से तत सम्बंधित अनुभव सर्टिफिकेट एवं एम्पैनेलमेंट सर्टिफिकेट संलग्न करें।

2- फर्म का सालाना टर्नओवर कम से कम रु. 40 लाख का होना चाहिए। इसके साक्ष्य के रूप में कृपया आयकर विवरणी /बैलेन्स शीट /जी एस टी रिटर्न /स्टेटमेंट ऑफ एकाउंट की प्रमाणित प्रति संलग्न करें।

Regional Office : 3 D Tashkant Marg Civil Line Allahabad 211001 (U.P.)  
E-mail: roalla@barodauprb.co.in; Fax-0532-2407653 Mo.7311121755,7311121764,






# बड़ौदा यू.पी.बैंक Baroda U.P. Bank

प्रधान कार्यालय : बुद्ध विहार व्यावसायिक योजना, तारामंडल, गोरखपुर-273016  
शिबिर कार्यालय : ए-1, सिविल लाइंस, रायबरेली-229001, फोन : 0535-2702075

- 3- बोली लगाने वाली फर्म का प्रयागराज में स्थानीय सर्विस सपोर्ट कार्यालय/ कैम्प कार्यालय होना अनिवार्य है।
- 4- दी गई कोटेशन 01 वर्ष हेतु वैध होगी तथा उक्त अवधि में फर्म द्वारा दी गयी दरों पर बैंक की आवश्यकतानुसार फर्म को आवंटित कार्य/ मद की आपूर्ति/ मरम्मत सम्बन्धी कार्यों को पूर्ण कराना होगा।
- 5 आपूर्ति आदेश के पश्चात् समस्त कार्यों को 30 दिनों (समस्त छुट्टियों को मिलाकर ) के भीतर निष्पादन सुनिश्चित करना होगा, अन्यथा की अवस्था में बैंक के पास अधिकार होगा कि कुल बिल में 5% प्रति सप्ताह अधिकतम 7.5% प्रति माह तक कटौती कर सकती है ।
- 6- कोटेशन/ टेन्डर प्रपत्र के साथ संलग्न Technical Specification में दिए गये नियम / मानकों के अनुसार ही आप द्वारा कार्य निष्पादन किया जायेगा तथा आप द्वारा लगायी गयी कोई भी शर्त बैंक द्वारा स्वीकार्य नहीं की जायेगी एवं टेन्डर के Technical Specification नियमों से विचलन स्वीकार्य नहीं होगा।
- 7- बैंक किसी भी समय कोटेशन / टेन्डर प्रक्रिया को निरस्त करने हेतु स्वतन्त्र है।
- 8- किसी भी प्रकार का स्पष्टीकरण टेन्डर प्रक्रिया के पूर्व किया जा सकता है।
- 9- ग्लो/साइन बोर्ड नॉन ग्लो साइन बोर्ड व इन्डिकेटर बोर्ड आदि की वारन्टी अवधि 5/10 वर्ष संलग्नक में दिए गये Technical Specification के अनुरूप होगी। वारन्टी अवधि में उक्त आपूर्ति में कमी अथवा खराबी होने पर टेन्डर को नयी आपूर्ति करनी होगी जिसका कोई अलग से भुगतान नहीं किया जायेगा।
- 10-टेन्डर प्राप्त करने वाली फर्म को टेंडर मनी रु० 50000/- की FDR 10 वर्षों के लिए बैंक के पास सिक्योरिटी मनी के रूप में रखना होगा, फर्म द्वारा टेंडर की शर्तों की अवहेलना की दशा में बैंक को उक्त टेंडर मनी को बिना नोटिस दिए जब्त करने का अधिकार होगा।
- 11- टेन्डर के साथ निम्न दस्तावेज प्रस्तुत करना होगा।  
टेन्डर दो अलग अलग लिफाफों, जिसमें एक लिफाफे के ऊपर Technical Bid एवं दूसरे लिफाफे जिस पर Financial Bid लिखा होगा।  
Technical Bid लिफाफे में रखे जाने वाले दस्तावेज निम्न हैं ।
  - a-Details of infrastructure for providing proper service and supply.
  - b-Attested photocopy of document of registration of firm along with GSTIN Number.
  - c-Photo copy of PAN Number duly attested.
  - d-Photo copy of income tax return for the last three years.
  - e- Certificate that the vendor is authorized dealer to sell said brand.

Regional Office : 3 D Tashkant Marg Civil Line Allahabad 211001 (U.P.)  
E-mail: roalla@barodauprrb.co.in; Fax-0532-2407653 Mo.7311121755,7311121764,





# बड़ौदा यू.पी. बैंक Baroda U.P. Bank

प्रधान कार्यालय : बुद्ध विहार व्यावसायिक योजना, तारामंडल, गोरखपुर-273016  
शिबिर कार्यालय : ए-1, सिविल लाईंस, रायबरेली-229001, फोन : 0535-2702075

f-The entire tender document duly signed by the vender as a mark of acceptance of term and conditions of the tender document.

g-All the documents should be self attested along with stamp of firm.

यदि उपरोक्त दस्तावेजों में से कोई भी दस्तावेज प्रस्तुत नहीं किया गया है तो टेन्डर निरस्त हो जायेगा और उसका Financial Bid नहीं खोला जायेगा।

**दूसरे लिफाफे Financial Bid में रखे जाने वाले दस्तावेज निम्न है**


Second Envelope must contain only Bid and nothing else.

- The price must be submitted on the prescribed format of Bill of Quantities (section A,B,C,D,E,F,G) along with document.
- Price bid will not be accepted on any other format or document.
- It must be clearly mentioned "PRICE BID OF 'DOCUMENT SUBMITTED FOR BID OF NEW SUPPLY & REPAIRING WORK OF SINAGE (GLOW SIGN BOARD)

दोनों लिफाफों को एक तीसरे लिफाफे में सीलबंद कर जिस पर (Document submitted for Bid of New supply & repairing work of Sinage (Glow Sign Board) लिखा होना चाहिए, दिनांक 09.03.2021 सायं 5.00 बजे तक उपरोक्त पते पर रजिस्टर्ड डाक अथवा स्वयं के द्वारा प्राप्त कराना सुनिश्चित करें उसके बाद प्राप्त किसी टेन्डर पर विचार नहीं किया जायेगा।

दिनांक :23.02.2021

क्षेत्रीय प्रबन्धक



Regional Office : 3 D Tashkant Marg Civil Line Allahabad 211001 (U.P.)  
E-mail: roalla@barodauprrb.co.in; Fax-0532-2407653 Mo.7311121755,7311121764,

## TECHNICAL SPECIFICATIONS FOR NEW SUPPLY (SUGGESTED)

### 1. SPECIFICATIONS FOR FLEX SUBSTRATE AND VINYL TO BE USED FOR SIGNAGE

I. **FASCIA-FLEXIBLE SUBSTRATE:** The properties are given in Table 1 below.

It shall have UV resistors added while manufacturing to prevent the whiteners turning yellow due to constant exposure to UV rays. The flex and Vinyl should be warranted for a period of five years from the date of completion against yellowing/graying of flex, plasticizer migration, wicking of flex, fungus or mildew formation, vinyl peel-off, fading, shrinkage, cracking and crazing etc.

II. **GRAPHICS:** Graphics shall be computer-cut with translucent vinyl matching the colour combination of Baroda U.P. Bank.

III. **The Colour specification for the signage :** Colour Pantone number (Baroda Vermillion) 1665C

IV. **Brand Make - 3M/Avery Dennison/LG Hausys/or Equivalent**

TABLE - 1 PHYSICAL PROPERTIES OF FLEXIBLE SUBSTRATE		
Property	Specification	Test Method
Thickness	600 micron +/- 10 %	- DIN 53353
Total Weight	700 gm/ sqmtr +/- 5 %	DIN 53353
Base Fabric	Polyester	
Yarn	1000 x 1000 Denier	DIN EN ISO 2060
Elongation	<50 %	ASTM 882
Tensile Strength (L/W)	150/ 140 Kg/ 2.5 CM	DIN 53354 (Cut Strip)
Tear Strength (L/W)	25 /20 Kg	DIN 53354 (Single Tongue)
Adhesion Strength (+PVC + Fabric)	50 Kg/ 5 Cm	DIN 53357
Light Transmission	25 to 32 %	
Substrate	Polyester scrim embedded in a white pigmented vinyl (or PVC based)	





TABLE -2 PHYSICAL PROPERTIES OF TRANSLUCENT VINYL		
Property	Specification	Test Method
Thickness (Including adhesive)	80m ± 10%	Micrometer
Tensile strength	400 ~ 1000 g/mm	ASTM 882
Elongation	100 ~ 300 %	ASTM 882
Peel adhesion(24hrs)	1,200g/in	180 peeling PSTC-1
Application temp.	10°C	18 to 25°C optimum, on clean substrate
Gloss	30 ± 5	@60, in Machine Direction (ASTM D 2457)
Dimensional Stability	Max 0.5%	Adhered to Aluminum Plate, Length Direction
		(100C Oven, 2hr , Average)
Release liner thickness	0.17mm ± 0.08mm	Micrometer
Colour	Baroda Vermillion - Pantone 1665 C	

**Note:-**


1. Written warranty shall be obtained for 5 years for per signage/site from the original manufacturer through vendors/ signage Contractor for Flex & Vinyl supply from date of installation. Vendors / Signage Contractor to submit tender specific authorization from Original Manufacturer for Flex / Vinyl.
2. Flex/ Vinyl Original Manufacturer should have presence in India either directly or through their subsidiaries by way of having its plants / sales offices in India.
3. Every signage warranty certificate submission shall be compulsory with execution invoice.
4. STANDARDS: All the materials shall conform to the required standards & safety aspects as specified in relevant ASTM/DIN/ BIS standards wherever applicable.
5. The sign boards have to be fixed at various heights from the ground level as per the requirement.

**2. SIGN BOX SPECIFICATIONS :**

- i. **SIGN CABINET STRUCTURE - FRAME WORK:** The Box (structure) should be fabricated using square MS tube 1" x 1" of 18 gauge (of Jindal, TATA or approved equivalent make) with primer and enamel painted. ISI grade GI Sheet of 24 gauge duly powder coated for side, top and bottom and 26 gauge for back should be used. Thickness of back-lit sign board should be minimum 9". Bird-proof vent holes to be provided on the GI sheets provided on the sides of the board to dissipate hot air. Aluminium drip cap with 2" projection to be provided on the top front edge of the sign board to protect the fascia from rain. All internal metal portions of the sign cabinet to be painted with one coat of Antirust paint and 2 coats of whitecolour enamel paint.




- ii. **SIGN CABINET SUPPORT:** The sign cabinet should be provided with suitable arrangements for fixing to existing wall surface or existing supporting structures available with suitable clamps, brackets, anchor bolts etc. The arrangements should be adequate to support the weight of the cabinet and to keep it firmly in position. The minimum requirement is that the signage frame work shall be anchored to the sunshade below using 'L' angle of 25mmx25mmx5mm thick equal angle in L shape at an interval of every 5 feet (of TATA, Jindal or equivalent approved make). Further the board should be anchored from top to the back wall using suitable steel/GI wire of minimum 8mm thick. All exposed clamps, brackets etc shall be painted with two coats of synthetic enamel paint over a coat of primer. Nothing extra will be paid for fixing the cabinet in position.
  - iii. **WELDING SPECIFICATIONS:** Branded welding rods should be used for welding the joints. Welding rod should be preheated prior to welding. Preheating the welding rods enables uniform & smooth flow of the welding material in the joints. If welding is done with preheated rod there will be no formation of open fissures in the joint due to smooth flow of welding material. Open fissures cause weakening of joints. Welding has to be done across the full cross section of the MS hollow pipe.
  - iv. **PROTECTION OF THE FRAME:** The entire frame of the sign cabinet post welding has to be grinded around the welding joints to remove spurs and undulations if any created during welding. Post grinding the joints, the MS pipe has to be painted with zinc chromate primer and 2 coats of synthetic enamel paint of white shade.
  - v. **FASTENERS:** The fasteners used shall be uniform and at such spacing that it does not spoil the appearance of the signage looking from the bottom or the sides. The head of the screw shall have capping of stainless steel.
  - vi. **SIGN BOX TENSIONING SYSTEM:** A suitable tensioning system should be used for stretching flexible substrate on the front part of the sign box such that there should not be any shrinkage, cracking and crazing. Flex wrinkling/ bends shall not occur post tensioning. To ensure that the flexible substrate is tensioned uniformly an extruded aluminum tensioning system with Allan key tensioning system with rubber beading should be adopted. The sign face shall be tensioned with tensioning system all along the length and width of the sign.
3. **PROCESS OF PASTING VINYL STICKERS OVER THE FLEX SUBSTRATE:**  
The pasting vinyl stickers over the flex substrate shall be undertaken with all care and techniques such as using pre mask tapes to the vinyl before initiating the fixing of the same over the flex, it shall be ensured that vinyl is properly aligned to the flex without any gaps at the outer edges, there are no air bubbles, etc., The workmanship shall be of high standards and engineering.
4. **FIXING OF THE SIGNAGES AND SAFETY AT SITE:** The signage providers shall duly assess the site condition for fixing securely by appropriate means using necessary clamp, hooks, fasteners and including minor civil works necessary at site. The entire signage so fixed at site shall withstand high wind pressures depending upon the actual locations / floor in which it is installed. It shall also be the responsibility of the signage solution provider for the safety of the installation, the signage till they accepted by the bank. While executing the work the labour force used shall comply to labour laws and all necessary safety measures shall be undertaken like using scaffolds, ladders, safety belts, helmets, gloves, appropriate tools. Suitable precautions shall be taken against overhead power lines, slippery surface or such other hazards which may be in the close proximity to the premises / site. Any damages to the signage during the process of installation will result in rejection of the signage and the same shall be replaced at their own cost.



5. ELECTRICAL COMPONENTS:

Specifications of Single Sided LED Modular Lights:


Sr. No.	Parameters	Significance	Desirables
Specifications for LED Module			
1	Make of LED Chip	To have creditable and quality products	Nichia/Cree/Lumileds/Osram
2	Make of LED Module	To have creditable and quality products	Osram/Lighting Technologies/Tridonic
3	LED Module Product Name	To have creditable and quality products	OsramBackLED M Plus G15/LT Maze SLHO/Tri doni cT ALEXChain Crystal Classic P541
4	Colour CCT	CCT defines the color which the light will Emit. 2000-3000K : Warm White; 3000-5000K : Day light color 6000-7000K : Pure white color ; >7000K : Cool white color	6500Kelvin(K)
5	Certifications of LED Chip	To check brightness	LM 80
6	Beam Angle	A beam angle defines the distance at which the module can be kept behind the vinyl to have uniform brightness	>=150 Degree (Angle of Irradiation)
7	Mounting Technology	LED Mounting - compactness by SMD Module Mounting - Modules should not come out with heating and wind pressure.	Surface Mounted Device (SMD)
8	Watt/Module	Wattage per module helps to calculate total power our signage will consume.	0.72 W/ 0.75 W
9	LED Module Per Sqft in Signage	To check no. of LED's used in a Signage.	3 Module/ Per Sqft



26	IP Rating	IP defines the protection of Modules for Dust and water	Min. IP67
27	Output Power		40W/60W/100W/120W
28	Standards for LED Driver	International standards.	CE ( European Conformity )/CB/C-Tick / UL (Underwritten laboratory) EN 55015, EN 62031 EN 61000-3-2 , EN 61000-33,, EN 61000-4-5, EN 61547, EN 61347-1, EN 61347-2-13 or As per IEC.
29	Cable for modules	Standard cable to avoid heat and fire.	AWG 18
30	Cable for drivers	Standard cable to avoid heat and fire.	AWG 18 / AWG 17
31	Warranty	To ensure quality and life of product.	5 Years warranty on LED modules and Drivers
32	THD (Total Harmonic Distortion)		< 10%
33	Short Circuit Protection		Automatic, Reversible
34	Over load Protection		Automatic, Reversible
35	Over temperature protection		Automatic, Reversible
36	UL/CE/ROHS/ENEC/BI S		Yes
37	Input Under Voltage		Shut down and auto- restart
38	Manufacturer		Osram/ Lighting Technologies/ Tridonic
<b>Protection Rating</b>		<b>Description</b>	
IP66		Fully protected from dust and protected against heavy seas or powerful jets of water	
IP67		Fully protected from dust and can also withstand being submerged in 1m (about 3.3 feet) of static water for up to 30 minutes	

**Note**

1. Written warranty shall be obtained for 5 years for per signage/site from the original Manufacturer through vendors/ signage Contractor for LED Modules & Power Supply from date of installation. Vendors / Signage Contractor to submit tender specific authorization from Original Manufacturer for LED Modules & Power Supply
2. Every signage warranty certificate submission shall be compulsory with execution invoice






26	IP Rating	IP defines the protection of Modules for Dust and water	Min. IP67
27	Output Power		40W/60W/100W/120W
28	Standards for LED Driver	International standards.	CE ( European Conformity )/CB/C-Tick / UL (Underwritten laboratory) EN 55015, EN 62031 EN 61000-3-2 ,EN 61000-33,, EN 61000-4-5, EN 61547, EN 61347-1, EN 61347-2-13 or As per IEC.
29	Cable for modules	Standard cable to avoid heat and fire.	AWG 18
30	Cable for drivers	Standard cable to avoid heat and fire.	AWG 18 / AWG 17
31	Warranty	To ensure quality and life of product.	5 Years warranty on LED modules and Drivers
32	THD (Total Harmonic Distortion)		< 10%
33	Short Circuit Protection		Automatic, Reversible
34	Over load Protection		Automatic, Reversible
35	Over temperature protection		Automatic, Reversible
36	UL/CE/ROHS/ENEC/BIS		Yes
37	Input Under Voltage		Shut down and auto- restart
38	Manufacturer		Osram/ Lighting Technologies/ Tridonic
<b>Protection Rating</b>		<b>Description</b>	
IP66		Fully protected from dust and protected against heavy seas or powerful jets of water	
IP67		Fully protected from dust and can also withstand being submerged in 1m (about 3.3 feet) of static water for up to 30 minutes	

**Note**

1. Written warranty shall be obtained for 5 years for per signage/site from the original Manufacturer through vendors/ signage Contractor for LED Modules & Power Supply from date of installation. Vendors / Signage Contractor to submit tender specific authorization from Original Manufacturer for LED Modules & Power Supply
2. Every signage warranty certificate submission shall be compulsory with execution invoice



3. STANDARDS: All the materials shall conform to the required standards & safety aspects as specified in relevant ASTM/BIS standards wherever applicable.
4. The sign boards have to be fixed at various heights from the ground level as per the requirement.

### 15. RETRO REFLECTIVE SIGN BOARDS & LOLLIPOP/INDICATOR BOARDS

#### Specification- Retro Reflective Sign Boards (Laminated)

Structure Pipe	1 inch
Sheet	Aluminium composite pannel (ACP) – 2 mm
Base	Retro Reflective sheet colour white
Retro sheet	HIP (High Intensity Prismatic), Type-4, Class B
Brand	3M, Avery Dennison, Conforming to ASTMD4956

#### Specification- Retro Reflective Lollipop/Indicator Boards (Laminated)- Double Side


ACP Sheet	2mm (3X2 feet, Rectangular shape)
Base	Retro Reflective sheet colour white
Retro sheet	HIP (High Intensity Prismatic), Type-4, Class B
Brand	3M, Avery Dennison, Conforming to ASTMD4956
M.S. Tee Section	Double M.S Tee section ISMT 50x50x6 mm of support length of 2500 mm

#### Specification- Vinyl Lollipop/Indicator Boards (Laminated) - Double Side

ACP Sheet	2mm (3X2 feet, Rectangular shape)
Base	Vinyl 3M (Scotchall 3630 series, 3650 series, 7725 series)
M.S. Tee Section	Double M.S Tee section ISMT 50x50x6 mm of support length of 2500 mm

#### Note :-

1. Written warranty shall be obtained for 10 years for per signage/site from the original Manufacturer through vendors/ signage Contractor for Retro Reflective Sign Boards/Indicator Boards and 5 years for Vinyl Indicator Boards per board/site from date of installation. Vendors / Signage Contractor to submit tender specific authorization from Original Manufacturer for ACP & Retro.
2. Every signage warranty certificate submission shall be compulsory with execution invoice
3. STANDARDS: All the materials shall conform to the required standards & safety aspects as specified in relevant ASTM/BIS standards wherever applicable.
4. The sign boards have to be fixed at various heights from the ground level as per the requirement.
5. References 10'X3', 12'X3', 15'X4', 20'X4' & 25' X 4'



## BILL OF QUANTITIES - SECTION- A (FOR NEW SIGNAGE WORK)


SI No	Description	QTY	Unit	Rate	Amount
<b>A</b>	<b>GLOW SIGN BOARD</b>				
1.1	Providing and Fixing of Flexible Substrate of make, respective codes and specifications given in tender for use in Back lit signages. Cost of fascia (Backlit flex) including labour charges for plotting & pasting, tensioning ("L" angle system) with signages cabinet, electrical items, Digital Timer and fixing complete as per specification. Replacement Warranty for the Fascia materials for a period of 5 years. The Parent Manufacturer/their representative has to inspect the site and certify for quality, workmanship and materials in the Warranty card.	1	S.Ft		
<b>a</b>	<b>SCAFFOLDING WORKS (No Extra charges for height below 25 ft )</b>				
	Cost of Scaffolding for Hoisting Signages, for height above 25 fts. (1) No payments will be made for scaffolding for Signage installations / fascia change up to a height of 25 feet from the floor level to bottom of Signage. 2) If the signage is to be installed on roof top of a building, where space for working is available, no extra payments will be paid for the sake of lift / scaffolding charges. The area of Scaffolding will be measured from the bottom of signage to Ground level x Length of signage	1	S.Ft.		

## BILL OF QUANTITIES FOR FASCIA CHANGE - SECTION-B

Sr.	Description	QTY	Unit	Rate	Amount(Rs.)
<b>B</b>	<b>REPLACING OF OLD FLEX &amp; VINYL OF EXISTING SIGNAGES (Backlit signage) (L1 WILL BE DECIDED FOR FLEX CHANGE RATE ONLY)</b>				
1.1	Removal of Old Flex and Vinyl and providing new flex and vinyl is using the present art work approved and retaining the existing Boxing / MS Framing. Replacement Warranty for the Fascia materials for a period of 5 years. The Parent Manufacturer / their representative has to inspect the site and certify for quality, workmanship and materials in the Warranty card.	1	S.Ft.		

Date :

Sign & Stamp of Vendor



**BILL OF QUANTITIES FOR NEW RETRO REFLECTIVE SIGN BOARDS - SECTION-C**

Sr.	Description	QTY	Unit	Rate	Amount(Rs.)
<b>C RETRO REFLECTIVE SIGN BOARDS</b>					
1.1	Manufacturing, supplying & installation of retro reflective sign boards made up of 2 mm thick aluminum sheet, face to be fully covered with high intensity encapsulated type heat activated retro reflective sheeting conforming to type-IV of ASTM-D 4956-01 in approved colour combination including subject matter, (bi-lingual), symbols and borders etc. as per IRC:67:2001, pasted on substrate by an adhesive backing which shall be activated by applying heat and pressure conforming to class -2 of ASTM-D- 4956-01 and fixing the same with suitable sized aluminium alloy rivets @ 20 cm c/c to back support frame of M.S. angle iron of size 25x25x3 mm along with theft resistant measures, mounted and fixed with 2 Nos. M.S. angles of size 35x35x5. Backside of aluminium sheet to be painted with two or more coats of epoxy paint over and including appropriate priming coat including all leads and lifts etc. Warranty for the Retro Reflective Signboard for a period of 10 years.	1	S.Ft.		

**BILL OF QUANTITIES FOR NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS - SECTION-D**


Sr.	Description	QTY	Unit	Rate	Amount(Rs.)
<b>D RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS-DOUBLE SIDE</b>					
1.1	Manufacturing, supplying & installation of retro reflective Lollipop/Indicator boards(double side) made up of 2 mm thick aluminium sheet(3X2 feet, Rectangular shape), Brand 3M, Avery Dennison, Conforming to ASTMD4956. with double M.S Tee section ISMT 50x50x6 mm of support length of 2500 mm. Warranty for boards for a period of 10 years.	1	S.Ft.		

**BILL OF QUANTITIES FOR NEW RETRO REFLECTIVE LOLLIPOP/INDICATOR BOARDS - SECTION-E**

Sr.	Description	QTY	Unit	Rate	Amount(Rs.)
<b>E VINYL LOLLIPOP/INDICATOR BOARDS-DOUBLE SIDE</b>					
1.1	Manufacturing, supplying & installation of Vinyl Lollipop / Indicator boards(double side) made up of 2mm ACP Sheet (3X2 feet, Rectangular shape), Vinyl 3M (Scotchcal 3630 series, 3650 series,7725 series) with double M.S Tee section ISMT 50x50x6 mm of support length of 2500 mm. Warranty for boards for a period of 5 years.	1	S.Ft.		

Date :

Sign & Stamp of Vendor



## BILL OF QUANTITIES FOR REPAIR & MAINTINANCE -SECTION -F

F	Providing and replacing of Electrical fitting & fixtures while replacing the Flex & Vinyl in case of damaged items. A sample quantity is mentioned below. Actual quantity as per site condition has to be replaced and got certified from the Branch head. No Extra charges for wiring Etc. will be paid.	Unit	Qty	Rate	Total Amount
1.1	LED Tube light-36 watt (PHILIPS/OSRAM/HAVELLS)	NOS	1		
1.2	LED TUBE LIGHT DRIVER(PHILIPS/OSRAM/HAVELLS)	NOS	1		
1.3	Installing of Digital timer (L&T/MDS)	NOS	1		
	<p><b>Tentative work to be carried out is as under-</b></p> <p>A (1.1) No of Piece 15 size (12x3)</p> <p>B (1.1)a. No of piece 10 size (10x3)</p> <p style="padding-left: 20px;">b. No of piece 10 size (12x3)</p> <p>C (1.1) No of piece 55 size (10x3)</p> <p>D (1.1) No of piece 100 size (3x2)</p> <p>The bidder will be finalized on the basis of total proposed tentative outgo according to the work to be carried out as above on the basis of rate quoted by the bidders.</p>				

GST shall be paid extra as applicable.

Note:-

1. No extra payment shall be made for lift up to 25 ft.(bottom of signages ) from floor level.
2. Scope of works at any location will be any one or more items from the above BOQ according to site condition.
3. Authorized Converter Certificate copy to be attached at the time of tender submission.
4. Vinyl/Flex/Retro Authorized distributor Material purchase order certificate to be produced at the time of invoice submission.
5. Flex/Vinyl/Retro Warranty certificate required at the time of invoice submission otherwise vendor payment will be hold by bank.
6. The Rates quoted will be valid for 1 Year . No Price Escalation will be considered.
7. Billing is based on actual square footage / quantity of the used material in Signages certified by the Branch concern person/ Branch Manager.

Date:

Sign & Stamp of Vendor

