



RO/KAND/05/P&E/2024-25/92

SHORT TERM TENDER NOTICE

(For Empanelled Furnishers & Interior Decorators only)

INTERIOR DECORATION WORK IN GAHLON BRANCH OF BARODA U.P. BANK

IMPORTANT DATES

DATE OF ISSUE OF TENDER NOTICE	22.07.2024
LAST DATE AND TIME OF SUBMISSION OF TENDER	14.08.2024 up to 05:00 P.M.
DATE OF OPENING OF TENDER (FINANCIAL BID)	16.08.2024 at 03:00 P.M.

Baroda U.P. Bank Regional office Kanpur Dehat Nabipur, Jainpur Kanpur Dehat 209311(U.P.)

Chief Manager

18

Date: 22.07.2024

NOTICE INVITING TENDER

Sealed item rate short term tenders are invited on behalf of the Regional Manager, Baroda U.P. Bank, from the Furnishers & Interior Decorators having valid Empanelment with the Baroda U.P. Bank for the work of INTERIOR DECORATION WORK IN GAHLON BRANCH OF BARODA U.P. BANK, Regional Office Kanpur Dehat.

Issue of tender documents

: 22/07/2024 to 14/08/2024

Last date of receipt of tender documents

: 14/08/2024 up to 5.00 PM

Date of opening of tender documents 3.

: 16/08/2024 at 03.00 PM

Place of submission & opening of tender

: Baroda U.P. Bank, REGIONAL OFFICE, KANPUR DEHAT

Period for completion of work from order date : Maximum 30 days 5.

6. Retention percentage : 10% (Ten percent) from final bill

Defect liability period

: 12 months from the date of completion certificate issued by the Bank Architect.

8. Release of retention money

: After 14 days from defect liability

period.

SUBMISSION OF TENDER

The tenders are to be submitted in a sealed envelope and clearly superscribed as "Tender for FURNISHING & INTERIOR DECORATION WORK IN GAHLON BRANCH OF BARODA U.P. BANK, REGIONAL OFFICE, KANPUR DEHAT.

- > Bids must be submitted through hand to hand or through registered Post.
- > The bid must contain two Envelopes as per procedure given below

FIRST ENVELOPE MUST CONTAIN ALL THE DOCUMENTS GIVEN BELOW:

- 1. Photo copy of PAN Number duly attested.
- 2. Photo copy of GST Number duly attested.
- 3. Registration certificate of both work i.e 'furniture & fixture work' and 'Electric & data cabling work
- 4. All the documents should be self attested along with stamp of the Firm.
- ➤ IT MUST BE MENTIONED ON ENVELOPE"DOCUMENT SUBMITTED FOR BID OF FURNISHING & INTERIOR DECORATION WORK IN GAHLON BRANCH".

SECOND ENVELOPE MUST CONTAIN ALL THE DOCUMENTS GIVEN BELOW:

SECOND ENVELOPE MUST CONTAIN only price bid and nothing else.

- > The price must be submitted on the prescribed format
- Price bid will not be accepted on any other format or document.
- ➤ It must be clearly mentioned "PRICE BID OF FURNISHING & INTERIOR DECORATION WORK IN GAHLON BRANCH".

BOTH TWO ENVELOPES MUST BE KEPT IN THIRD SEALED ENVELOPE AND SUPERSCRIBED"BID FURNISHING & INTERIOR DECORATION WORK IN GAHLON BRANCH".

GENERAL INSTRUCTIONS TO TENDERERS

Time of Work Completion- One Month (From the date of work order)

- The work as detailed in this tender shall be executed and completed in all respects within one month in
 accordance with the Tender Document, Bill of Quantities, Drawings and Instructions, to the satisfaction of the
 Architects and the Bank. A penalty of 1% per day of total work awarded will be imposed for delay in work
 completion.
- 2. The term "Contractor" shall mean the successful tenderer to whom the Contract shall be awarded.
- 3. The Contractor should quote the rates in figures and words. Any corrections or Over-writing should be initialed by the Contractor.
- 4. The Contractor should submit the tenders with seal, signature and date on each Page.
- 5. The Contractors should submit the cost of the main items as per tender specifications. Further modification after awarding of the contract shall be not allowed unless there is specific instruction

- by the Bank/Architect to change specifications.
- 6. The contract is time-bound and the works are to be completed within the time limit specified in the notice inviting tenders. This is a working office and the contractor has to work with no or minimum obstruction to its regular services.
- 7. The decision of Employer and the Architect is final and binding.
- 8. The contractor must submit registration certificate of both work i.e 'furniture & fixture work' and 'Electric & data cabling work' in separates envelope must be mention "Technical Bid for furnishing & electrical work".
- 9. The contractor must submit the tender for both work i.e 'furniture & fixture work' and 'Electric & data cabling work', Partially filled tender will be rejected.
- 10. For Electrical fixtures and light points required as per drawings the contractor has to draw the wires from the existing positions of light points, power points wherever and if applicable. The contractor shall submit the certificate from electrical contractor holding required license/certification from directorate of electrical safety (U.P.)/competent authority of any other State.

TERMS & CONDITIONS

- Unless otherwise mentioned, all works are with no allowance for Lapse waste. Unless
 otherwise described or measured separately, price for all the items shall include all
 necessary straight & curved edges.
- 2. Any damage to the work before the site is handed over, is to be replaced or made good at the expense of the contractor to the entire satisfaction of the Architect/Bank.
- 3. Income Tax, Other Tax as applicable shall be deducted at source as per the Income Tax Act / Rules.
- 4. The quantities indicated are subject to change. The payment of the bill shall be made as per the actual measurement as certified by the architect but not exceeding the total value quoted in the tender form.
- 5. The Architect or any officer of the Employers will be free to inspect the work at the site during the period of execution. Any suggestion of change or modification to improve the quality of work will be carried out subject to prior approval of the competent authority of the employers and that of the Architect.
- Incase of failure to take up the work even after accepting the work order, or leaving the
 work incomplete, or for defective work not rectified, or violation of the terms and
 conditions, the contractor will be de-panelled/blacklisted.
- 7. For any item of work not covered or any unforeseen items of work, payment will be made according to the rates approved for similar nature of work, the costing done by the Architect, as per current PWD schedule of rates, or as per analysis of material cost, labour rate and profit to the Contractor at 10%. The Contractor must obtain prior approval in writing before undertaking such additional works.

- 8. The tenderers shall sign each & every page of the tender documents including the drawings attached here to.
- The amount is to be quoted in figures as well as in words. In case the rates quoted in words and in figures are in variance, the amount written in words shall be taken as final.
- 10. The Contractor shall make their own arrangement at their own cost for storing materials, plants, tools etc. The employers will not be liable for security of the Contractor's materials.
- 11. No tools or plants will be issued by the bank.
- 12. The Employer / Architect reserves the right to accept or reject any tender without assigning any reason whatsoever and the said decision shall be final and binding upon the tenderer.
- 13. In case of breach of contract by the Contractor for slow progress of works or any other claim of damage, the Employer or the Architect may have the power to rescind the contract without furnishing further reasons thereof.
- 14. The Architect shall have the power to ask the contractor to furnish the sample/ color / test certificate from any Govt. /Authorized agent for any materials used/ to be used in the Works, the expenditure of which is to be borne by the Contractor.
- 15. The Employer shall be not be liable for any damages or compensation payable as a consequence of any accident or injury to any workman or other persons in the employment of the Contractor or any sub-contractor.
- 16. On completion of the Works, all rubbish, debris, materials, tools, Laborers, etc. to be removed by the contractor from the site and the contractor will hand over the site clean & clear & in usable condition within 3 days of completion of the works. Failing this, the employer may
- 17. Dispose the materials at the cost of the contractor.
- 18. In case of any dispute, the matter will be referred to the Regional Manager, Baroda U.P. Bank, Regional Office Kanpur Dehat (UP).
- 19. Final Payment after completion of Project will be done with the certificate of Architect with deduction of retention money by the Bank.
- 20. The rates quoted in the tender shall exclude GST but include all excise tax, No escalation of rates will be allowed under any circumstances.

DETAILED ESTIMATE / SPECIFICATION FOR BILL OF QUANTITIES OF FURNISHING WORK FOR BARODA UP BANK BRANCH AT GAHLO

	OF FURNISHING WORK FOR BARODA UP BANK		I AT GAHLO		
Sl.no	Description of items	Unit	Qty.	Rate	Amount
4	Computerised Ledger & Cash Counter				
	Providing and placing in position ledger counter with top, vertical sides/dividers, skirting and fascia made out of 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) on all exposed surfaces. It shall also have 75mm x 40mm teak wood runners below the top and for footrest below. Every unit shall be provided with a side unit (size - W-500mm, H-750mm, D-500mm approx.), consisting of 150 mm deep drawer at top and a cabinet with open able/hinged shutter below.				
	The fascia of drawer and shutter of cabinet below shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The side unit shall have CAM locks, handles, guides, sliding units, hinges, magnetic catcher's etc. of approved make. Every unit shall be provided with a keyboard drawer unit (size - W-550mm, H-100mm, D-300mm approx.) below. The counter shall have 100mm deep fascia, below the top, in which keyboard drawer unit shall be adjusted.				
	It shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The unit shall have CAM locks, handles, guides, sliding units etc. of approved make. The job shall include for 6mm x 6mm grooves in between sides and open able drawers and hinged shutters. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be with 1mm thick laminate, all complete to the satisfaction of the Architect.				
_	775-L Y	D6	5		
a	High Level	Rft	5		
	High level (two levels) Computerised cash counter. Lower level top shall be 900mm wide and at 750mm level from floor & upper level top shall be 250mm wide (and at 1150 mm level from floor				
		D.C.			V
ь	Low Level	Rft	9		
	Low level (two levels) Computerised ledger counter. Lower level top shall be 900mm wide and at 750mm level from floor & upper level top shall be 150mm wide and at 900mm level from floor				
_					
5	Solid full height partition both side Laminated For unglazed partitions, no glazing to be given in partition/doors & other	Sft			
	specifications as below 9. (note: in case of false ceiling, the vertical TW members to be fixed with pucca ceiling but the area of partition payable will be below the false ceiling only.)				
				ě.	
6	Partly glazed partition for cash cabins Decorative Grill (12mm thk)-hexagonal opening as per instruction of Bank's Engineer/Architect.) All exposed edges of Plywood shall be fixed with 1/8" C.P.Teak	Sft	135		
	Lipping. Providing and fixing of Cash Enclosures at height of 7'-4" with Anodized aluminium frame work, heavy sections (2mm thickness) of 2"x1.5", spacing of 2'0"x2'0" on bothsides and covered 6mm thick BWR plywood finished with 1mm thick laminate of blue, red colours for skriting & borders. Partition shall have provision for opening and 19mm BWR plywood tray for challan receiving purpose. Cost include aluminium grill and fixed with teak wood beading and duco paint. Cost also include 3 Nos of Solid core flush Doors with sizes of 2'6"x7"0", fixed in the partition. Door shall have teak wood beading and lipping with duco paint. Door finished with 1mm thick laminate of white colour for base and red & blue for skirting of approved pattern. Door shall have 8mm glass fixed with teak wood beading and duco paint. Rate to include hardware's like brass hinges, godrej three nos of night latch, door closure, door stopper and handles. Cost also include cash transaction opening shall be provided with door arrangements made with BWR plywood frame work finished by laminate, duco paint and locking system. Cost include wastages, transports, loading, unloading charges, labours, materials, tools, lead, lift and etc.Complete as per drawings and instructions of the Architect.			6	
					E

		T	-		
4	I dead less height partition	Sft	100		
10	artly glazed low height partition ame specification as in 1 but P/F half height partition of height 3'-6" with				
	goden laminate till 3'-0" and 1'-6" height 12 mm thick glass secured with D				
1,5	rackets including all hardware necessary with the same specs.as above.				
1	racheto mounts	-1			
	and the second s	Sft	125	-	
F	Providing and fixing Wall Panelling consisting of 2" x1 " 18 gauge section	192000			•
F	placed at 2'0x2'-0" horizontally and vertically with Unannodised Allumnium lize 1.5mm thick of JINDAL/ INDAL confirming to ISI 303 standard as internal	1			
S	rame structure (as per site requirement) framework. The framing shall be fixed				1
İ	rame structure (as per site requirement) framework MDF of approved make firmly with with 8mm thick MR grade ply + 6 mm MDF of approved make firmly				
- 1:	to the eluminium frame on either side finished with Illin in (ingli-				
1	crewd to the administration from the control of the administration				
1	ixing 12x12mm steem beech wood beading				
1	making 6 mm grooves complete with polish & melamine spray finish on wood				
- 1.	average as per architectural drawings finished with 1mm tiller				
١,	leading them includes providing and fixing 100mm wide skirting of 1111111				
1	thick mettallic laminate as per approved sample. Note: Surface measurement				
1	for one face & visible areas below false ceiling will be made for payment.				
-					KVIII.
	Manager's table + Side Table with 12mm thk glass top	Each	1		
+	Providing and fixing in position manager's table of size 6'-0"x2'6" as per	77.0			
- 1	drawing no including side storage (credenzalby using 25 mm thick plywood)				
- 1	contact and 19 mm thick playond for all other horzontal and vertical members.				
	Telegopie CPII stand/ready made keyboard tray shall be provided of approved				Ť.
- 1	model and make. Footrest made with TW member of size 4"x1 ½ " finished with				
	french polish as per.				
	· ·				
-	drawing shall be provided. Facia of side storage(credenza) shall be finished				
	with 1 mm thick laminates as shown in the drawing and all other sides shall				
- 1	be finished with white enamel paint. The side storage (credenza) shall be				
J	provided with handles (stainless steel finish) and channels as per approval of				
- /	the project consultant/bank . all exposed plywood surfaces to be finished with				
	1 mm thick . laminates of approved make and shade and all exposed edges of table top and ply verticals to have 1" x 1/4" TW lipping , all exposed TW section			22	
	table top and ply verticals to have 1 x 74 1 w hipping, an exposed to be melamined and internal surfaces to have with 1mm thick laminate.				
	to be melamined and internal surfaces to have with that the littings in litem to include plywood boxing, all necessary hardware and fittings in		9		
	stainless steel finish, lipping to all edgs etc. complete in all respect.				
	stainless steer linish, apparig to all coge etc.				
_	Officer table + Side Table with 12mm thk glass top	Each			
10	5'-0"x2'-6")+Side table				
	a and iffection as shove	Sft	205		
1	Full height storage / low height storage/ back storage (credenza)				4
_	Providing and fixing in position full height storage / low height storage / back				
	land (and ange) as shown in drawing no. (8) [9] and [10] respectively using	1	l.		
	I have defrequired thickness finished with 1 mm thick laminates as shown in	i .			
	the drawing and all other sides shall be timished with white ename paint as				
	detailed therein.			1	
	The storage units shall be provided with handles (stainless steel finish) as per				
	approval of the project consultant/bank.				- 0
	approval of the project consultant, same				
		J 6000		17	1
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of				
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4"				
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4" TW lipping . all exposed TW section to be melamined in matching colour laminate and interpret surfaces to have with 1mm thick laminate. item to				
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4" TW lipping. all exposed TW section to be melamined in matching colour laminate and internal surfaces to have with 1mm thick laminate. item to include all processory bardware an fittings in stainless steel finish., Godrej				I P
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4" TW lipping. all exposed TW section to be melamined in matching colour laminate and internal surfaces to have with 1mm thick laminate. item to include all processory bardware an fittings in stainless steel finish., Godrej				
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4" TW lipping . all exposed TW section to be melamined in matching colour laminate and interpret surfaces to have with 1mm thick laminate. item to				
	All exposed plywood surfaces to be finished with 1 mm thick. Laminate of approved make and shade and all exposed edges of plywood to have 1"x1/4" TW lipping . all exposed TW section to be melamined in matching colour laminate and internal surfaces to have with 1mm thick laminate. item to include all necessary hardware an fittings in stainless steel finish ., Godrej multi purpose locks including magnetic ball catcher etc. complete in all				

1XX	Providing & fixing 12 m.m. glass in front of cash cabin and front counters with brass clamps including cut out for passing currency as/details. The edges of the glass to be machine polished.	Sq. ft.	45		
s	Public settee size 60"x 18"x18" Teak wood ,19 mm thick board, 1.00 mm thick mica GL/VL teak wood beeding including cost of all material, labour tools and plant etc. with 3" foam sleep well 32 density and covering cloth of superior quality.	No	1		
		No	1		
15	Suggestion box Public writing wall stand (including cost of fitting) 36"x16"x9" 19mm Board, 1.00 mm thick mica, teak wood beeding, Polish/Paint with fitting.	No	1		
16	Notice Board	1.00	NOS		
	Notice Board Providing and fixing in position notice board (as per design) of size - 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick Premium Board (Green /Century) with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces. It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts.				
	It shall also have 19mm wide two track aluminium channel for sliding arrangement, all around, along with locking arrangement.board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make- Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm) frame work. It shall be covered with 6mm thick Premium ply (Green /Century), on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect.	9	1		
17	Check drop box	Sqft	1		
18	Center Table with teak wood and 10mm glass ISI(size 48"x24"x18")				
19	UPS PARTITION WITH BISON BOARD HT REST SPECIFICATION AS PER ASPER ABOVE PARTITION	S Sqft	40	Total Rs.	

Not: GST Will be charged Extra

Approved manufacturers / suppliers C.I. (Dulex - Duco) / Asian paints / Goodlac Nerolac BWR- Century/Green/Archid only Premium quality BWR- Century/Green / Archid only Premium quality
BWR- Century/Green/Archid only Premium quality
BWR- Century/Green/Archid only Premium quality
BWR- Century/Green /Archid only Premium quality
Armstrong , Indian gypsum board
Sunmica/ Archid/Century/Green 1mm thick as per bank approved color
G.K.W./Nettle fold
Fevical SH
Godrei
Godrej
Jindal
Modi/Asahi/Saint Gobain
Eurobond/Altobond/Alukbond
EBCO
EBCO
EBCO
Jhonsions Perlto
Vista, Luxaflex

	PROJECT - ESTIMATE FOR ELECTRICAL W BANK - BARODA UP BANK BRANCH-GAHLO				
	DADWOW ADG	77.14	lo.	In.	
NO	A -Electrical wiring (All switches to be Modular type - Anchor/ Havells or equivalent approved by architect)	Unit	Qty	Rate	Amount
1	Light & Fan points Supply & Installation of concealed point wiring using 600v grade 3x1.5 Sq.mm copper conductor PVC insulated wires (with proper R.Y.B color code) pulled through heavy gauge 19mm PVC conduit pipe heavy duty concealed in wall/floor/panelling/partitions or above false ceiling as per requirement including 2 Nos. 2.5 sqmm circuit wires from the relevant DB and also including 1.5 sqmm green color copper earth wire and switch plate, switches, etc. as approved by the Bank's Engineer/Architect. All switch & sokets shall be modular type complete with cover plate & GI/MS box. The work shall also include for cutting chase for conduits and moulded boxes, if required, in the wall/floor (Without damaging the building/wall) along with clamping the conduit at every 600mm interval & finally finishing the surface & matching the same with the existing surface. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the Bank.	•			
	Light points + AFF points including the cost of 6A switch	Point	30		
ь	Ceiling Fan Point including the cost of 6A Switch along with electronic	Point	7		
c	regulator Wall Fan Point along with 6A switch	Point	1		
d	6A switch & Socket on SDb	Point	7		
2	RAW POWER POINT		-		
4	Single Power Points - Supply & Installation of point wiring for Raw power plug points on workstations / table for computers using 2 X2.5 + 1x1.5 Sq.mm copper conductor PVC sheathed flexible wire pulled through heavy gauge 19mm PVC conduit pipe heavy duty concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. Each point consisting of 1 nos of 16A, 2/3/5 pin sockets & 1 No.16A Switch wired together forming one point. The earth wire of green color only. All switch & sokets shall be modular type complete with cover plate & GI/MS box. The work shall also include for cutting chase for conduits and moulded boxes, if required, in the wall/ floor (Without damaging the building/wall) along with clamping the conduit at every 600mm interval & finally finishing the surface & matching the same with the existing surface. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc. The job shall be complete & to the entire satisfaction of the Bank.	Point	6		
A	Sub Main Wiring/ Cabling - : SITC of sub main wiring 4nos. 10 sq.mm Stranded copper wires for UPS Input from main incoming panel to incoming Db of UPS power input system etc. in 25mm dia PVC haevy duty conduit complete to the satisfaction of the bank.	ЈОВ	1		
В	UPS Power Input System: SITC of 4way TPN Double door Db IP 42 horizontal Complete with 1no. Incoming 32A. TP MCB and 3 x 32A 2P MCB's to regulate supply for UPS complete in all respect as required and to the satisfaction of the bank.	Set	1		
С	Wiring for UPS Input & UPS Output (For both Critical 2Kva & Non- Critical 3Kva UPS) with 2x4.0sq.mm + 1x 1.5sq.mm stranded Cu. conductor (Finolex /Anchor /Skytone) to be laid in 19mm PVC pipe heavy duty/ Flexible pipe laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc.The job shall be complete & to the entire satisfaction of the Bank.	JOB	1		
D	S/F of 32A 2P MCB in 2way metallic box including proper connectionbs thru lugs. Both the Db's shall be inter looped- Qty included in item 3. (2nos. For ATM and 2nos. For Branch)	Each	1		
E	UPS Output Power Distribution System: SITC of 12 way SPN Db Double door IP -43 Siemens make with 32A DP 10kA MCB and 09 nos. SP 10kA MCB complete in all respect and as required & to the satisfaction of the bank. Siemens/	Set	1		
F	Input Wiring for UPS Db's with 2x4.0sq.mm + 1x 1.5sq.mm stranded Cu. conductor (Finolex /Anchor /Skytone) to be laid in 19mm PVC pipe heavy duty/ Flexible pipe laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement. The rate should include the cost of all materials, labour, T&P, taxes & levies, scaffolding, shifting of furniture, carting away the debris and cleaning the floor etc.The job shall be complete & to the entire satisfaction of the Bank	ЈОВ	1		
)	Supply & fixing of 4nos. 6A switches & sockets (Modular type c/w MS/GI box & cover plate) complete with computer point circuit wiring with 2x2.5sq.mm + 1x 1sq.mm stranded Cu. Single core Copper conductor (Finolex/Anchor/RPG) to be laid in PVC conduit 1" dia/ vertical drops heavy duty laid & concealed in wall/ floor/ panelling/ partitions or above false ceiling as per requirement.	Per Node	6		
4					
	MAIN INCOMING DANCE & DISTRIBUTION				A
5 A	MAIN INCOMING PANEL & DISTRIBUTION SITC of 100A Kit kats fuse unit 3nos in wooden patra complete with 100Amp. Neutral link complete in all respect as required. 1 No for Metre	Set	1		

в	Main Incoming Panel				
-	Supply, Installation, Testing & Commissioning of main			5	
	distribution board panel fabricated of 18swg (powder coated) comprising of	Nos.	1		
	distribution board panel labricated of foswg (powder course)	200,000			
-	Indicator lamps 3 nos.				
-	Voltmeter & ammeter(one each)				
-	Rotary selector switches 2 nos for voltmeter & ammeter				No.
_	Busbar (each of RYB +N) copper 100 amp each		-		
-	125 Amp MCCB(Siemens/ L&T/ ABB/ Schnider) incoming 3P adjustable 25kA		- E		
	125 Amp MCCB(Siemens/ Loc1/ ABB) Schilder) incoming of acquisition Bolist				
-	Changeover TPN 100 amp for DG set (Havells/ ABB/ Sochomac)		E.		
-	Outgoing 63A 3P MCB's - 6 nos.				
-	Outgoing 32Amp 2P MCB's - 6 nos.	1			
_	Earth bus bar 25x5mm Gl strip - 2nos. At the bottom.	3			
_	Earth bus bar 25x5mm GI strip - 2nos. At the bottom.	3			
_	Supply Installation testing & commissioning of XLPE insulated Armoured		(= = =		7
6	Al.codutctor cable between main panel & DB's & generator of required				
- 1	Al. codute tor cable between main paner & DB's & generator of required thickness of approved make Skytone/ Havells based on the load assessment &				
-	thickness of approved make Skytone/ Havens based on the load assessment of				1
	confirmation of the same with architect. This rates include cost of lugs at both		-		
_	the ends 3.5 x50 sq.mm cable from Meter to Kit kat to the main panel & Pole (Aprrox -	105			1
	20 mtr	JOB	1		
-	4c x20 sq.mm cable from Main Panel TO LHS DB (Aprrox - 20 mtr)	JOB	1		
-	4c x 20 sq.mm cable from Main Panel to RHS DB (Aprrox - 20 mtr)	JOB	1		
-	4c x 20 sq.mm cable from Main Panel to Kikat (Generator) (Aprrox - 40 mtr)	JOB	1		
	4c x 20 sq.min cable from Main Fairer to Mina (4-11-11-11)	JOB	T		
		1			
7	Supply, installtion, testing & commissioning of VTPN Db double door with MCB				
	as incomer IP 42 complete in all respects for AC, PP and L & F as under -			1	
	Siemens/ Hager/ Lagrand/ ABB			to a second	
A	RHS 6way VTPN db - Loaction RHS wall opposite Cash cabins (From entrance	1			
•	to Rear record room & Toilet area) - Siemens 8GB0406VRC or equivalent			1	
	to Rear record room & rollet area) - Stelliens oobovoovice or equivalent				
_	Incomer - 63A 3P MCB 10kA adjustable neutral to be directly connected to	Each	1		
	neutral bus	Each	1		
-	3no. 32A 1P-MCBs 10 KA - AC's - 2nos. RHS & 1rear				
_	3no. 16A 1P-MCBs 10 KA - for single power points - 2 cash & 1 May I help				
		100			
	You & 2nos. D/W 4nos. 10A 1P-MCBs 10 KA for L&F				
-	40s. 6A 1P-MCBs 10 KA for L&F				
-	Blanking Plates - 2no.				
_	All connections to be terminated thru lugs				The state of
-	All connections to be terminated thru rugs				The state of the s
В	LHS 6way VTPN db - Loaction LHS wall behidn advance (From LHS LV Cash to				
	Man Day Sigmons SCR0406VPC or equivalent	-	9-3		
_	Incomer - 63A 3P MCB 10kA adjustable neutral to be directly connected to	Each	1		
	neutral bus	Lach	1	30	
-	4o. 32A 1P-MCBs 10 KA - AC's - 3nos. LHS & 1 Mgr Rm	1		4.	
-	4no. 16A 1P-MCBs 10 KA - for single power points - (LV cash, 2 CRE,				
	1Advance, 2 MR & 2 Router				
_					
Ξ	2nos. 10A 1P-MCBs 10 KA for L&F 2os. 6A 1P-MCBs 10 KA for L&F		1	N Section 1	

- 14	ll connections to be terminated thru lugs					
+	in connections to be terminated that and					
		-				31
F e s c s j c c l l r t t l l	C-EARTHING For Main Panel - S/burying of Dual pipe technology (Pipe in Pipe) earthing deterrode having GI 80mm O/D pipe with 25 micron coating, 3metres long. The space between two pipes to be filled with Highly conducive & Non corrosive themical compound. The installation shall be thru earth auger. The vacant space between pipe & hole shall also be filled with compound all around. The ob also includes S/F of GI strip clamp with two holes (with SS/GI bolts & nuts) on the electrode & taking two earthing leads of 25 x 5 mm GI strip (Assumed ength of 10m - beyond 10m to be paid extra) upto Main panel complete in all respects with guaranteed E/N voltage of less than 3 volts and resistance less han 1 ohms. The distance between two earthing pits to be 10ft or more NCLUDING Earth wire 4 sq mm copper wire . Approx -80 mtr (2 FOR BRANCH & 1 ATM)	Per Icn.	2			
1		7				
	F - FIXTURES & FITTINGS al Supplying and fixing Philips make 36W LED FLAT PANEL after disconnection of existing fitting 2'x2' size in grid type false ceiling, 600x600 suitable for recess mounting, CRCA sheet, asthetic looking, or equ Philips/havells	Each				
	b) Supplying and fixing Philips make or eqv 10 W LED round type downlighter (Philips/ wipro /Jaguar)	Each				
	Supply installation testing and commissioning of 1*20watt Batten type tubular LED light fitting with LEDs, driver, diffuser, and housing complete in all respects in UPS room and record /wc/bath room /suitable place with complete in all respect with required color on need basis.	Each	24			
1	C. W. Jaka	Each	4			
	S/F of angle holder for bulbs including cost of 11w CFL lamp for Toilets	2				
- 1	i) Supply & installation of wall bracket fan 450 MM (Heavy duty/ high speed) Make Bajaj/cropmton greaves/havells/Orient (to be supplied after consultation with architect/Electrical Engineer as per approved drawing)	Each				
7	g) Supply & fixing of the 1200 mm 48") Sweep Ceiling fan (Orient PSPO/crompton greaves/havells) with downward rod(below false ceiling), canopy etc. including of PVC flexible copper wire.(white colour)(High speed) (Warranty Cerificate is necessary)with downward rod, circular boxes, ball sockets, ceiling plates, suitable arm bracket etc. including connection with wire)White colour (WITH REGULATOR)	Each	7			
G	Supply & Fixing of fresh air fan 12" - Crompton Greaves/ Usha/ Khaitan/ Baiai	Each	2			
		SET	0			
Н	e) Supplying and fixing LED strip 3000 K 24 watt 5 mtr length with driver [Philips or Havells or Cormpton]	-	100000	- Carrier		
	(Philips or Havells or Cormpton)					
2	e) Supplying and fixing LED strip 3000 K 24 watt 5 mtr length with driver [Philips or Havells or Cormpton] 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e [as directed by Architect from Server to Switch, Switch to computer I/O data socket as required complete in all respects] in 25mm dia rigid PVC conduit [including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects.	Each	6			
2	Philips or Havells or Cormpton \\ 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer I/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a subjective distance of 3ft from pipes laid down for power distribution) including	Each				
2 A B	Philips or Havells or Cormpton 1 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer I/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link	Each	6	8		
2 A	Philips or Havells or Cormpton 1 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make	Each Each Each	6			
B D E	Philips or Havells or Cormpton 1 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make	Each Each Each Each	6	8.		
B D E	I - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of 9 U wall mounted rack c/w fan etc as required	Each Each Each	6			
B B F F	I - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of 9 U wall mounted rack c/w fan etc as required S/F of Cable Manager as required GRAND TOTAL AMOUNT (gst extra) List of approved materials Materials	Each Each Each Each	6 6 1 1 1 0 0 Approv	legrands, ABB,	urers/supplier	
2 2 A A B B C C D D F F	Philips or Havells or Cormpton I - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of 9 U wall mounted rack c/w fan etc as required S/F of Cable Manager as required GRAND TOTAL AMOUNT (gst extra) List of approved materials Materials MCCB	Each Each Each Each	6 6 1 1 1 0 0 Approv	legrands, ABB, GE/ Standard s	, GE, SIEMENS stangaurd	
2 2 A A B B C C F F 1 2 2	Philips or Havells or Cormpton 1 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of Cable Manager as required GRAND TOTAL AMOUNT (gst extra) List of approved materials Materials MCCB Changeover	Each Each Each Each	6 6 1 1 1 0 0 MDS	legrands, ABB, GE/ Standard s / Standard / In	, GE, SIEMENS stangaurd ndo Asian / HP	L
B C F	Philips or Havells or Cormpton 1 - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of 9 U wall mounted rack c/w fan etc as required S/F of Cable Manager as required GRAND TOTAL AMOUNT (gst extra) List of approved materials Materials MCCB Changeover Distribution board	Each Each Each Each	6 6 1 1 1 0 0 MDS (MDS MDS MDS MDS MDS MDS MDS MDS MDS MDS	legrands, ABB, GE/ Standard s / Standard / In / Standard / In	, GE, SIEMENS stangaurd ndo Asian / HP ndo Asian / HP	L
2 2 A A B B B F F F T 2 3 3 4 4 5 5	I - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of 9 U wall mounted rack c/w fan etc as required S/F of Cable Manager as required GRAND TOTAL AMOUNT (gst extra) List of approved materials Materials MCCB Changeover Distribution board MCB Cable	Each Each Each Each	6 6 1 1 1 0 0 MDS (MDS MDS MDS MDS MDS MDS MDS MDS MDS MDS	legrands, ABB, GE/ Standard s / Standard / In / Standard / In ster / Rallison	, GE, SIEMENS stangaurd ndo Asian / HP ndo Asian / HP / Incab / CCI	L
B B C C D D E F F 3 3 4	I - DATA CABLING Supply & Fixing of XL RJ 45 toolless information outlet with Duplex face plate with dual connectors Grey colour cat 6e including cost of supplying & laying CAT 6e (as directed by Architect from Server to Switch, Switch to computer 1/O data socket as required complete in all respects) in 25mm dia rigid PVC conduit (including laying of Gl draw wire complete with junction box, circular box, elbows, bends & other accessories as required by chase cutting on floor, wall, through partition or over false ceiling. The data cabling pipe should be laid at a minimum distance of 3ft from pipes laid down for power distribution) including interconnection with connectors as required complete in all respects. Supply & fixing of 7ft Grey colour Patch chord Giga speed Systimax/ D link make Supply & fixing of 3ft Grey colour Patch chord Giga speed Systimax/ D link make S/F of 24Port Jack Panel fully loaded systimex make S/F of Gable Manager as required GRAND TOTAL AMOUNT (gst extra) List of approved materials Materials MCCB Changeover Distribution board MCB Cable Copper wire	Each Each Each Each	6 6 1 1 1 0 0 MDS (MDS MDS MDS MDS MDS MDS MDS MDS MDS MDS	legrands, ABB, GE/ Standard s / Standard / In / Standard / In	, GE, SIEMENS stangaurd ndo Asian / HP ndo Asian / HP / Incab / CCI nchor	L

	AT GAHL	O BRANCH
S.No.	DESCRIPTION	AMOUNT (Rs.)
1	FURNISHING WORK	
2	ELECTRICAL WORK	
e v	TOTAL (Rs.)	

