



बड़ौदा यू.पी.बैंक Baroda U.P. Bank

प्रधान कार्यालय : बुद्ध विहार व्यावसायिक योजना, तारामंडल, गोरखपुर-273016
शिबिर कार्यालय : ए-1, सिविल लाइंस, रायबरेली-229001, फोन : 0535-2702075

प्रयागराज क्षेत्र अन्तर्गत आने वाली शाखाओं हेतु ग्लो साइन बोर्ड /नॉन ग्लो साइन बोर्ड व इन्डिकेटर बोर्ड हेतु निविदा

अवगत कराना है कि हमारे क्षेत्रान्तर्गत 87 शाखाओं व क्षेत्रीय कार्यालय की आवश्यकता के अनुसार पूर्व में लगे ग्लो साइन बोर्ड/ नॉन ग्लो साइन बोर्ड व इन्डिकेटर बोर्ड के स्थान पर बैंक के निर्धारित मानको के अनुसार नवगठित बैंक "बड़ौदा यू.पी.बैंक" के नाम व लोगो के Glow Sign Board,Fascia Change,Retro reflective Sign Board,Retro Reflective Lollipop-Indicator Board (Double Side), Vinyl Lollipop Indicator Board-(Double Side) आदि के Installation, Repairing & Maintenance का कार्य कराया जाना है।

इस पत्र के साथ संलग्न Technical Specification के अनुसार पूर्ण रूप से भरा हुआ अपना कोटेशन सीलबन्द लिफाफे में दिनांक 05.02.2021 को सायंकाल 5:00 बजे तक इस कार्यालय को निम्न पते पर उपलब्ध कराएँ। उक्त तिथि के पश्चात् प्राप्त कोटेशन पर विचार नहीं किया जायेगा। टेन्डर दिनांक 06.02.2021 को सायं 4.00 बजे क्षेत्रीय कार्यालय में खोला जायेगा।

बड़ौदा यू.पी.बैंक

क्षेत्रीय कार्यालय 3D ताशकंद मार्ग सिविल लाइन्स प्रयागराज (इलाहाबाद) 211001

टेन्डर प्रक्रिया के पश्चात् Successfull bidder को उपरोक्त कार्य के सापेक्ष बैंक द्वारा दिए गये मानको के अनुसार आवश्यक Items की संस्थापना के पश्चात् वारंटी अवधि हेतु Invoice मूल्य की 5 प्रतिशत राशि को रिटेंशन मनी के रूप में रोकते हुए नियमानुसार टी डी एस की कटौती करते हुए भुगतान किया जायेगा।

अन्य शर्तें निम्नवत हैं -

- 1- उक्त कार्य हेतु किसी बैंक अथवा सरकारी संस्था में कम से कम 3 वर्षों का अनुभव होना चाहिए, एवम विभिन्न बैंकों /संस्थानों से तत सम्बंधित अनुभव सर्टिफिकेट एवं एम्प्लोयमेंट सर्टिफिकेट संलग्न करें।
- 2- फर्म का सालाना टर्नओवर कम से कम 40 लाख का होना चाहिए। इसके साक्ष्य के रूप में कृपया आयकर विवरणी /बैलेन्स शीट /जी एस टी रिटर्न /स्टेटमेंट ऑफ एकाउंट की प्रमाणित प्रति संलग्न करें।
- 3- बोली लगाने वाली फर्म का प्रयागराज में स्थानीय सर्विस सपोर्ट कार्यालय/ कैम्प कार्यालय होना अनिवार्य है।
- 4- दी गई कोटेशन 01 वर्ष हेतु वैध होगी तथा उक्त अवधि में फर्म द्वारा दी गयी दरों पर बैंक की आवश्यकतानुसार फर्म को आवंटित कार्य/ मद की आपूर्ति/ मरम्मत सम्बन्धी कार्यों को पूर्ण कराना होगा।

Regional Office : 3 D Tashkant Marg Civil Line Allahabad 211001 (U.P.)
E-mail: roalla@barodauprrb.co.in; Fax-0532-2407653 Mo.7311121755,7311121764,



बड़ौदा यू.पी.बैंक Baroda U.P. Bank

प्रधान कार्यालय : बुद्ध विहार व्यावसायिक योजना, तारामंडल, गोरखपुर-273016
शिनिर कार्यालय : ए-1, सिविल लाईंस, रायबरेली-229001, फोन : 0535-2702075

5 आपूर्ति आदेश के पश्चात् समस्त कार्यों को 30 दिनों (समस्त छुट्टियों को मिलाकर) के भीतर निष्पादन सुनिश्चित करना होगा, अन्यथा की अवस्था में बैंक के पास अधिकार होगा कि कुल बिल में 5% प्रति सप्ताह अधिकतम 7.5% प्रति माह तक कटौती कर सकती है।

6- कोटेशन/ टेन्डर प्रपत्र के साथ संलग्न Technical Specification में दिए गये नियम / मानकों के अनुसार ही आप द्वारा कार्य निष्पादन किया जायेगा तथा आप द्वारा लगायी गयी कोई भी शर्त बैंक द्वारा स्वीकार्य नहीं की जायेगी एवं टेन्डर के Technical Specification नियमों से विचलन स्वीकार्य नहीं होगा।

7- बैंक किसी भी समय कोटेशन / टेन्डर प्रक्रिया को निरस्त करने हेतु स्वतन्त्र है।

8- किसी भी प्रकार का स्पष्टीकरण टेन्डर प्रक्रिया के पूर्व किया जा सकता है।

9- ग्लो/साइन बोर्ड नॉन ग्लो साइन बोर्ड व इन्डिकेटर बोर्ड आदि की वारन्टी अवधि 5/10 वर्ष संलग्नक में दिए गये Technical Specification के अनुरूप होगी। वारन्टी अवधि में उक्त आपूर्ति में कमी अथवा खराबी होने पर टेन्डर को नयी आपूर्ति करनी होगी जिसका कोई अलग से भुगतान नहीं किया जायेगा।

10-टेन्डर प्राप्त करने वाली फर्म को टेंडर मनी रु० 50000/- की FDR 10 वर्षों के लिए बैंक के पास सिक्क्योरिटी मनी के रूप में रखना होगा, फर्म द्वारा टेंडर की शर्तों की अवहेलना की दशा में बैंक को उक्त टेंडर मनी को बिना नोटिस दिए जब्त करने का अधिकार होगा।

11- टेन्डर के साथ निम्न दस्तावेज प्रस्तुत करना होगा।

a-Details of infrastructure for providing proper service and supply.

b-Attested photocopy of document of registration of firm along with GSTIN Number.

c-Photo copy of PAN Number duly attested.

d-Photo copy of GSTIN No. duly attested.

e-Photo copy of income tax return for the last three years.

f-The entire tender document duly signed by the vender as a mark of acceptance of term and conditions of the tender document.

g-All the documents should be self attested along with stamp of firm.

दिनांक :15.01.2021


क्षेत्रीय प्रबन्धक



Regional Office : 3 D Tashkant Marg Civil Line Allahabad 211001 (U.P.)
E-mail: roalla@barodauprb.co.in; Fax-0532-2407653 Mo.7311121755,7311121764,

TECHNICAL SPECIFICATIONS FOR NEW SUPPLY (SUGGESTED)

1. SPECIFICATIONS FOR FLEX SUBSTRATE AND VINYL TO BE USED FOR SIGNAGE

I. **FASCIA-FLEXIBLE SUBSTRATE:** The properties are given in Table 1 below.

It shall have UV resistors added while manufacturing to prevent the whiteners turning yellow due to constant exposure to UV rays. The flex and Vinyl should be warranted for a period of five years from the date of completion against yellowing/graying of flex, plasticizer migration, wicking of flex, fungus or mildew formation, vinyl peel-off, fading, shrinkage, cracking and crazing etc.

II. **GRAPHICS:** Graphics shall be computer-cut with translucent vinyl matching the colour combination of Baroda U.P. Bank.

III. **The Colour specification for the signage :** Colour Pantone number (Baroda Vermillion) 1665C

IV. **Brand Make - 3M/Avery Dennison/LG Hausys/or Equivalent**

TABLE - 1 PHYSICAL PROPERTIES OF FLEXIBLE SUBSTRATE		
Property	Specification	Test Method
Thickness	600 micron +/- 10 %	~ DIN 53353
Total Weight	700 gm/ sqmtr +/- 5 %	DIN 53353
Base Fabric	Polyester	
Yarn	1000 x 1000 Denier	DIN EN ISO 2060
Elongation	<50 %	ASTM 882
Tensile Strength (L/W)	150/ 140 Kg/ 2.5 CM	DIN 53354 (Cut Strip)
Tear Strength (L/W)	25 /20 Kg	DIN 53354 (Single Tongue)
Adhesion Strength (PVC + Fabric)	50 Kg/ 5 Cm	DIN 53357
Light Transmission	25 to 32 %	
Substrate	Polyester scrim embedded in a white pigmented vinyl (or PVC based)	

TABLE -2 PHYSICAL PROPERTIES OF TRANSLUCENT VINYL		
Property	Specification	Test Method
Thickness (Including adhesive)	80m ± 10%	Micrometer
Tensile strength	400 ~ 1000 g/mm	ASTM 882
Elongation	100 ~ 300 %	ASTM 882
Peel adhesion(24hrs)	1,200g/in	180 peeling PSTC-1
Application temp.	10°C	18 to 25°C optimum, on clean substrate
Gloss	30 ± 5	@60, in Machine Direction (ASTM D 2457)
Dimensional Stability	Max 0.5%	Adhered to Aluminum Plate, Length Direction (100C Oven, 2hr , Average)
Release liner thickness	0.17mm ± 0.08mm	Micrometer
Colour	Baroda Vermillion - Pantone 1665 C	

Note:-

1. Written warranty shall be obtained for 5 years for per signage/site from the original manufacturer through vendors/ signage Contractor for Flex & Vinyl supply from date of installation. Vendors / Signage Contractor to submit tender specific authorization from Original Manufacturer for Flex / Vinyl.
2. Flex/ Vinyl Original Manufacturer should have presence in India either directly or through their subsidiaries by way of having its plants / sales offices in India.
3. Every signage warranty certificate submission shall be compulsory with execution invoice.
4. STANDARDS: All the materials shall conform to the required standards & safety aspects as specified in relevant ASTM/DIN/ BIS standards wherever applicable.
5. The sign boards have to be fixed at various heights from the ground level as per the requirement.

2. SIGN BOX SPECIFICATIONS :

- i. **SIGN CABINET STRUCTURE - FRAME WORK:** The Box (structure) should be fabricated using square MS tube 1" x 1" of 18 gauge (of Jindal, TATA or approved equivalent make) with primer and enamel painted. ISI grade GI Sheet of 24 gauge duly powder coated for side, top and bottom and 26 gauge for back should be used. Thickness of back-lit sign board should be minimum 9". Bird-proof vent holes to be provided on the GI sheets provided on the sides of the board to dissipate hot air. Aluminium drip cap with 2" projection to be provided on the top front edge of the sign board to protect the fascia from rain. All internal metal portions of the sign cabinet to be painted with one coat of Antirust paint and 2 coats of whitecolour enamel paint.

- ii. **SIGN CABINET SUPPORT:** The sign cabinet should be provided with suitable arrangements for fixing to existing wall surface or existing supporting structures available with suitable clamps, brackets, anchor bolts etc. The arrangements should be adequate to support the weight of the cabinet and to keep it firmly in position. The minimum requirement is that the signage frame work shall be anchored to the sunshade below using 'L' angle of 25mmx25mmx5mm thick equal angle in L shape at an interval of every 5 feet (of TATA, Jindal or equivalent approved make). Further the board should be anchored from top to the back wall using suitable steel/GI wire of minimum 8mm thick. All exposed clamps, brackets etc shall be painted with two coats of synthetic enamel paint over a coat of primer. Nothing extra will be paid for fixing the cabinet in position.
 - iii. **WELDING SPECIFICATIONS:** Branded welding rods should be used for welding the joints. Welding rod should be preheated prior to welding. Preheating the welding rods enables uniform & smooth flow of the welding material in the joints. If welding is done with preheated rod there will be no formation of open fissures in the joint due to smooth flow of welding material. Open fissures cause weakening of joints. Welding has to be done across the full cross section of the MS hollow pipe.
 - iv. **PROTECTION OF THE FRAME:** The entire frame of the sign cabinet post welding has to be grinded around the welding joints to remove spurs and undulations if any created during welding. Post grinding the joints, the MS pipe has to be painted with zinc chromate primer and 2 coats of synthetic enamel paint of white shade.
 - v. **FASTENERS:** The fasteners used shall be uniform and at such spacing that it does not spoil the appearance of the signage looking from the bottom or the sides. The head of the screw shall have capping of stainless steel.
 - vi. **SIGN BOX TENSIONING SYSTEM:** A suitable tensioning system should be used for stretching flexible substrate on the front part of the sign box such that there should not be any shrinkage, cracking and crazing. Flex wrinkling/ bends shall not occur post tensioning. To ensure that the flexible substrate is tensioned uniformly an extruded aluminum tensioning system with Allan key tensioning system with rubber beading should be adopted. The sign face shall be tensioned with tensioning system all along the length and width of the sign.
3. **PROCESS OF PASTING VINYL STICKERS OVER THE FLEX.SUBSTRATE:**

The pasting vinyl stickers over the flex substrate shall be undertaken with all care and techniques such as using pre mask tapes to the vinyl before initiating the fixing of the same over the flex, it shall be ensured that vinyl is properly aligned to the flex without any gaps at the outer edges, there are no air bubbles, etc., The workmanship shall be of high standards and engineering.
 4. **FIXING OF THE SIGNAGES AND SAFETY AT SITE:** The signage providers shall duly assess the site condition for fixing securely by appropriate means using necessary clamp, hooks, fasteners and including minor civil works necessary at site. The entire signage so fixed at site shall withstand high wind pressures depending upon the actual locations / floor in which it is installed. It shall also be the responsibility of the signage solution provider for the safety of the installation, the signage till they accepted by the bank. While executing the work the labour force used shall comply to labour laws and all necessary safety measures shall be undertaken like using scaffolds, ladders, safety belts, helmets, gloves, appropriate tools. Suitable precautions shall be taken against overhead power lines, slippery surface or such other hazards which may be in the close proximity to the premises / site. Any damages to the signage during the process of installation will result in rejection of the signage and the same shall be replaced at their own cost.

5. ELECTRICAL COMPONENTS:

Specifications of Single Sided LED Modular Lights:

Sr. No.	Parameters	Significance	Desirables
Specifications for LED Module			
1	Make of LED Chip	To have creditable and quality products	Nichia/Cree/Lumileds/Osram
2	Make of LED Module	To have creditable and quality products	Osram/Lighting Technologies/Tridonic
3	LED Module Product Name	To have creditable and quality products	OsramBackLED M Plus G15/LT Maze SLHO/Tridonic ALEXchain Crystal Classic P541
4	Colour CCT	CCT defines the color which the light will Emit. 2000-3000K : Warm White; 3000-5000K : Day light color 6000-7000K : Pure white color ; >7000K : Cool white color	6500Kelvin(K)
5	Certifications of LED Chip	To check brightness	LM 80
6	Beam Angle	A beam angle defines the distance at which the module can be kept behind the vinyl to have uniform brightness	>=150 Degree (Angle of Irradiation)
7	Mounting Technology	LED Mounting - compactness by SMD Module Mounting - Modules should not come out with heating and wind pressure.	Surface Mounted Device (SMD)
8	Watt/Module	Wattage per module helps to calculate total power our signage will consume.	0.72 W/ 0.75 W
9	LED Module Per Sqft in Signage	To check no. of LED's used in a Signage.	3 Module/ Per Sqft

10	System efficacy (Lm/W) or Lumin Output	It is a measure of the efficiency of a lighting system.	>95-100 Lm/W
11	Operating temperature	To ensure proper functioning of signages at various locations.	-40 degree C to + 65 degree Centigrade
12	LED Module life	It indicates the number of hours before the luminance drops to 70% of initial output.	Min 50000 Burning Hrs (L70/B50) at 85 degree Centigrade
13	Housing Module Material	Housing module material selected for holding the LED chip and lens.	Poly carbonate (PC) / RoHS (Reduction of hazardous substances) Compliant material to be used.
14	CRI (Colour Rendering Index)	The color rendering index (CRI) is the index of LED tube light compared with natural light.	>=80
15	Protection Class	IP defines the protection of Modules for Dust and water	IP66
16	Certifications & Standards for Modules	No Hazardous substance and meeting international standard.	BIS/LM79/LM80
17	LED Module Certification		Yes
18	Internal drivers in modules		Yes
19	Optics		The chip should have an optical lens.
Specifications for LED Driver			
20	LED Driver	Converts I/P AC voltage to DC voltage for LEDs.	Osram/Lighting Technologies/Tridonic
21	LED Driver Name	Converts I/P AC voltage to DC voltage for LEDs.	Osram OptotronicSeries/Lighting Technologies (LT)/Tridonic TALEXX converter
22	Driver Wattage (W)	Wattage at which driver is designed.	40W/60W/100W/120W
23	Surge protection (in KV inbuilt)	To protect the system from fluctuation in voltage.	Inbuilt Min 6 KV (Line to ground)
24	Supply voltage for drivers (Input Voltage)	Voltage range at which LED driver s function.	90 V-300 V
25	Protection		Over Voltage, Over Current, Over Temperature, Short circuit.

26	IP Rating	IP defines the protection of Modules for Dust and water	Min. IP67
27	Output Power		40W/60W/100W/120W
28	Standards for LED Driver	International standards.	CE (European Conformity)/CB/C-Tick / UL (Underwritten laboratory) EN 55015,EN 62031 EN 61000-3-2 ,EN 61000-33,, EN 61000-4-5, EN 61547, EN 61347-1, EN 61347-2-13 or As per IEC.
29	Cable for modules	Standard cable to avoid heat and fire.	AWG 18
30	Cable for drivers	Standard cable to avoid heat and fire.	AWG 18 / AWG 17
31	Warranty	To ensure quality and life of product.	5 Years warranty on LED modules and Drivers
32	THD (Total Harmonic Distortion)		< 10%
33	Short Circuit Protection		Automatic, Reversible
34	Over load Protection		Automatic, Reversible
35	Over temperature protection		Automatic, Reversible
36	UL/CE/ROHS/ENEC/BI S		Yes
37	Input Under Voltage		Shut down and auto- restart
38	Manufacturer		Osram/ Lighting Technologies/ Tridonic
Protection Rating		Description	
IP66		Fully protected from dust and protected against heavy seas or powerful jets of water	
IP67		Fully protected from dust and can also withstand being submerged in 1m (about 3.3 feet) of static water for up to 30 minutes	

Note

1. Written warranty shall be obtained for 5 years for per signage/site from the original Manufacturer through vendors/ signage Contractor for LED Modules & Power Supply from date of installation. Vendors / Signage Contractor to submit tender specific authorization from Original Manufacturer for LED Modules & Power Supply
2. Every signage warranty certificate submission shall be compulsory with execution invoice

